




Husqvarna K 970 Ring

The Husqvarna K 970 Ring has a cutting depth of 260 mm, twice the amount of a traditional power cutter. The K 970 Ring has a high cutting capacity, can make deep cuts from one side and is the quickest method for cutting small and medium-sized bores because no time is lost on installing rails. The power-to-weight ratio is first rate and features SmartCarb™, a built-in automatic filter compensation and a highly efficient vibration dampening system. The K 970 Ring is also equipped with an X-Torq® engine, which reduces emissions up to 75 % and lowers fuel consumption by 20 % and DuraStarter™, a dust-sealed starter that boosts reliability and product life. Air Purge and a decompression valve make it very easy to start.



Features Husqvarna K 970 Ring

- All models are equipped with a Poly-V belt, for better transmission of power, far longer product life and extended service intervals.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To enable the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- Cutting depth of 260 mm, twice the depth of a traditional blade.
- Engine with X-Torq produces 75 % less emissions, 20 % lower fuel consumption and more power.
- DuraStarter™, the dust-sealed starter, and the durable starter cord reduce the risk of downtime and increase reliability and product life.
- SmartCarb™, built-in automatic filter compensation, maintains high power and lowers fuel consumption.
- Easy to start thanks to Air Purge and decompression valve.
- The Poly-V belt provides better transmission of power, less frequent re-tensioning and greatly extended product life.
- DEX – water-saving wet cutting kit for efficient dust management.
- Fuel indicator in the tank shows fuel level, to help avoid unnecessary stoppages.

| TECHNICAL SPECIFICATION | |
|---------------------------------------|----------------------------|
| Engine | Air-cooled 2 stroke engine |
| Cylinder displacement | 93,6 cm ³ |
| Power output | 4,8 kW |
| Fuel tank volume | 1 lit |
| Idling speed | 2700 rpm |
| Vibrations front handle | 3,8 m/s ² |
| Vibrations rear handle | 5,1 m/s ² |
| Sound pressure level at operators ear | 103 dB(A) |
| Sound power level, guaranteed (LWA) | 116 dB(A) |
| Blade diameter | 350 mm |
| Max cutting depth | 260 mm |
| Weight (excl. cutting equipment) | 13,6 kg |
| Fuel tank volume | 1 lit |

 **Husqvarna**®

 **YOUNG/MAN
RICHARDSON
& CO. LTD.**

6 - 10 Parkway Drive, Mairangi Bay, Auckland 0632
Ph: 09 443 2436 Auck Ph: 03 341 6923 Chch

www.yrco.co.nz