HiPERHARD - Lithium Densifier Husqvarna New Zealand Limited

Chemwatch: **5427-21** Version No: **3.1.1.1** Safety Data Sheet according to HSNO Regulations Chemwatch Hazard Alert Code: 2

Issue Date: 07/10/2020 Print Date: 12/10/2020 L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

| Product Identifier | |
|-------------------------------|-------------------------------|
| Product name | HiPERHARD - Lithium Densifier |
| Synonyms | Concrete densifier. |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Penetrating sealer for strengthening and hardening of concrete surfaces and other masonry building materials.

Details of the supplier of the safety data sheet

| Registered company name | Husqvarna New Zealand Limited |
|-------------------------|--|
| Address | 51 Aintree Avenue Mangere, Auckland 2022 New Zealand |
| Telephone | +64 9 920 2410 |
| Fax | +64 9 920 2429 |
| Website | http://www.husqvarna.com/nz/ |
| Email | customer.service@husqvarna.co.nz |

Emergency telephone number

| Association / Organisation | CHEMWATCH EMERGENCY RESPONSE |
|-----------------------------------|------------------------------|
| Emergency telephone numbers | +61 2 9186 1132 |
| Other emergency telephone numbers | +64 800 700 112 |

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

| Classification ^[1] | Skin Corrosion/Irritation Category 2, Eye Irritation Category 2 | |
|--|---|--|
| Legend: | 1. Classified by Chernwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI | |
| Determined by Chemwatch using GHS/HSNO criteria | 6.3A, 6.4A | |

Label elements



Signal word Warning

Hazard statement(s)

| H315 | Causes skin irritation. |
|------|--------------------------------|
| H319 | Causes serious eye irritation. |
| | |

Precautionary statement(s) Prevention

| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
|------|--|
|------|--|

| Precautionary statement(s) Response | | |
|-------------------------------------|--|--|
| P321 | Specific treatment (see advice on this label). | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |

HiPERHARD - Lithium Densifier

| P337+P313 | If eye irritation persists: Get medical advice/attention. |
|-----------|---|
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|---------------|-----------|--|
| Not Available | | chemical entity containing |
| Not Available | <20 | lithium silicates |
| Not Available | balance | Ingredients determined not to be hazardous |

SECTION 4 First aid measures

Description of first aid measures

| Eye Contact | If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|--|
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Advice for firefighters

| ······································ | |
|--|--|
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. |

HiPERHARD - Lithium Densifier

| Fire/Explosion Hazard | Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. May emit corrosive fumes. Decomposes on heating and produces: carbon monoxide (CO) carbon dioxide (CO2) silicon dioxide (SiO2) |
|-----------------------|---|
|-----------------------|---|

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. |
|--------------|---|
| Major Spills | Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. DO NOT allow clothing wet with material to stay in contact with skin |
|-------------------|---|
| Other information | Store under 25 deg C. Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

Conditions for safe storage, including any incompatibilities

| Suitable container Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. | |
|--|------------|
| Storage incompatibility | None known |

SECTION 8 Exposure controls / personal protection

| Control parameters | | | | | | |
|------------------------------------|---------------|---------------|---------------|---------------|--|--|
| Occupational Exposure Limits (OEL) | | | | | | |
| INGREDIENT DATA | | | | | | |
| Not Available | | | | | | |
| Emergency Limits | | | | | | |
| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 | | |
| HiPERHARD - Lithium Densifier | Not Available | Not Available | Not Available | Not Available | | |
| Ingredient | Original IDLH | · | Revised IDLH | | | |
| HiPERHARD - Lithium Densifier | Not Available | | Not Available | | | |

Continued...

HiPERHARD - Lithium Densifier

| sure controls | | | | | |
|-------------------------------------|---|--|--|--|--|
| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. | | | | |
| Personal protection | | | | | |
| Eye and face protection | Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed a clean environment only after workers have washed hands thoroughly. | | | | |
| Skin protection | See Hand protection below | | | | |
| Hands/feet protection | Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. | | | | |
| Body protection | See Other protection below | | | | |
| Other protection | Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit. | | | | |

Respiratory protection

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or
- vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- ▶ Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | rance Colourless liquid, mixes with water. | | | | |
|--|--|---|----------------|--|--|
| Physical state | Liquid | Relative density (Water = 1) | 1.03-1.05 | | |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available | | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available | | |
| pH (as supplied) | 10-11 | Decomposition temperature | Not Available | | |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available | | |
| Initial boiling point and boiling range (°C) | 100 | Molecular weight (g/mol) | Not Applicable | | |
| Flash point (°C) | Not Available | Taste | Not Available | | |
| Evaporation rate | Not Available | Explosive properties | Not Available | | |
| Flammability | Not Available | Oxidising properties | Not Available | | |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available | | |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available | | |
| Vapour pressure (kPa) | 2.33 @ 20 deg C | Gas group | Not Available | | |

| Chemwatch: 5427-21 Catalogue Number: | | Page 5 of 7 HiPERHARD - Lithium Densifier | | Issue Date: 07/10/2020 Print Date: 12/10/2020 |
|--|---|--|--|--|
| Version No: 3.1.1.1 | 1 | | | |

| Solubility in water | Miscible | pH as a solution (1%) | Not Available |
|--------------------------|------------|-----------------------|---------------|
| Vapour density (Air = 1) | >1 (water) | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 | | | |
|-------------------------------------|---|--|--|--|
| Chemical stability | nstable in the presence of incompatible materials. roduct is considered stable. azardous polymerisation will not occur. | | | |
| Possibility of hazardous reactions | See section 7 | | | |
| Conditions to avoid | See section 7 | | | |
| Incompatible materials | e section 7 | | | |
| Hazardous decomposition products | e section 5 | | | |

SECTION 11 Toxicological information

Information on toxicological effects

| Inhaled | Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. | | | | |
|--|---|--|---|--|--|
| Ingestion | May cause gastric irritation. Accidental ingestion of the material may be damaging to the health of the individual. | | | | |
| Skin Contact | Evidence exists, or practical experience predicts, that the following direct contact, and/or produces significant inflau inflammation being present twenty-four hours or more af repeated exposure; this may result in a form of contact d and swelling (oedema) which may progress to blistering may be intercellular oedema of the spongy layer of the s The material may accentuate any pre-existing dermatitis Open cuts, abraded or irritated skin should not be expos Entry into the blood-stream through, for example, cuts, a Examine the skin prior to the use of the material and ens | Immation when applied to the healt fter the end of the exposure period dermatitis (nonallergic). The derma (vesiculation), scaling and thicken skin (spongiosis) and intracellular of s condition sed to this material abrasions, puncture wounds or lesi | hy intact skin of animals, for up to four hours, such Skin irritation may also be present after prolonged o itits is often characterised by skin redness (erythema) ng of the epidermis. At the microscopic level there edema of the epidermis. | | |
| | Evidence exists, or practical experience predicts, that the | e material may cause eye irritation | in a substantial number of individuals and/or may | | |
| Eye | produce significant ocular lesions which are present twei Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot | ation characterised by temporary re | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva | | |
| Eye Chronic | Repeated or prolonged eye contact may cause inflamma | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to here minimised as a matter of course. | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. | | |
| Chronic | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be in Prolonged or repeated skin contact may cause drying with | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to hear minimised as a matter of course. ith cracking, irritation and possible | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. | | |
| | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be a | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to here minimised as a matter of course. | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. | | |
| Chronic HiPERHARD - Lithium | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be i Prolonged or repeated skin contact may cause drying wi | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to hear minimised as a matter of course. ith cracking, irritation and possible IRRITATION Not Available ances - Acute toxicity 2.* Value obdition | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. Alth (as classified by EC Directives using animal dermatitis following. | | |
| Chronic HiPERHARD - Lithium Densifier | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be Prolonged or repeated skin contact may cause drying wi TOXICITY Not Available 1. Value obtained from Europe ECHA Registered Substa | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to hear minimised as a matter of course. ith cracking, irritation and possible IRRITATION Not Available ances - Acute toxicity 2.* Value obdition | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. Alth (as classified by EC Directives using animal dermatitis following. | | |
| Chronic HiPERHARD - Lithium Densifier <i>Legend</i> : | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be Prolonged or repeated skin contact may cause drying wi TOXICITY Not Available 1. Value obtained from Europe ECHA Registered Substa specified data extracted from RTECS - Register of Toxic | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to here minimised as a matter of course. ith cracking, irritation and possible IRRITATION Not Available ances - Acute toxicity 2.* Value observed of chemical Substances | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. Alth (as classified by EC Directives using animal dermatitis following. ained from manufacturer's SDS. Unless otherwise | | |
| Chronic HiPERHARD - Lithium Densifier <i>Legend:</i> Acute Toxicity | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ot Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be Prolonged or repeated skin contact may cause drying wi TOXICITY Not Available 1. Value obtained from Europe ECHA Registered Substa specified data extracted from RTECS - Register of Toxic | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to hear minimised as a matter of course. ith cracking, irritation and possible IRRITATION Not Available ances - Acute toxicity 2.* Value ob c Effect of chemical Substances Carcinogenicity | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. Alth (as classified by EC Directives using animal dermatitis following. ained from manufacturer's SDS. Unless otherwise | | |
| Chronic HiPERHARD - Lithium Densifier <i>Legend:</i> Acute Toxicity Skin Irritation/Corrosion | Repeated or prolonged eye contact may cause inflamma (conjunctivitis); temporary impairment of vision and/or ott Long-term exposure to the product is not thought to prod models); nevertheless exposure by all routes should be to Prolonged or repeated skin contact may cause drying with TOXICITY Not Available 1. Value obtained from Europe ECHA Registered Substate specified data extracted from RTECS - Register of Toxic | ation characterised by temporary re ther transient eye damage/ulceration duce chronic effects adverse to hear minimised as a matter of course. ith cracking, irritation and possible IRRITATION Not Available ances - Acute toxicity 2.* Value obto Effect of chemical Substances Carcinogenicity Reproductivity | tion into the eye(s) of experimental animals. edness (similar to windburn) of the conjunctiva in may occur. Alth (as classified by EC Directives using animal dermatitis following. ained from manufacturer's SDS. Unless otherwise X X X X X | | |

Data either not available or does not fill the criteria for of
 Data available to make classification

SECTION 12 Ecological information

| oxicity | | | | | | |
|----------------------------------|---|--------------------|---------------|------------------|------------------|--|
| | Endpoint | Test Duration (hr) | Species | Value | Source | |
| HiPERHARD - Lithium Densifier | Not Available | Not Available | Not Available | Not Available | Not Available | |
| Legend: | Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Su V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessmer Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data | | | | | |

Version No: 3.1.1.1

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air | | |
|---------------------------|---------------------------------------|---------------------------------------|--|--|
| | No Data available for all ingredients | No Data available for all ingredients | | |
| | | | | |
| Bioaccumulative potential | | | | |
| Ingredient | Bioaccumulation | | | |
| | No Data available for all ingredients | | | |
| | | | | |
| Mobility in soil | | | | |
| Ingredient | Mobility | | | |
| | No Data available for all ingredients | | | |

SECTION 13 Disposal considerations

| Waste treatment methods | |
|------------------------------|---|
| Product / Packaging disposal | DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. |

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

| Labels Required | |
|------------------|----------------|
| Marine Pollutant | NO |
| HAZCHEM | Not Applicable |

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard | |
|------------|---|--|
| HSR002544 | Construction Products (Subsidiary Hazard) Group Standard 2017 | |

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Quantity (Closed Containers) | Quantity (Open Containers) |
|----------------|------------------------------|----------------------------|
| Not Applicable | Not Applicable | Not Applicable |

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Class of substance | Quantities |
|--------------------|----------------|
| Not Applicable | Not Applicable |

HiPERHARD - Lithium Densifier

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

| National Inventory | Status |
|--------------------------------|--|
| Australia - AIIC | Yes |
| Australia - Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | Yes |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - ARIPS | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 Other information

| Revision Date | 07/10/2020 |
|---------------|------------|
| Initial Date | 30/09/2020 |

SDS Version Summary

| Version | Issue Date | Sections Updated |
|---------|------------|----------------------|
| 3.1.1.1 | 07/10/2020 | Classification, Name |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.