2021 Product Guide





WELLINGTON



CHRISTCHURCH



ACCESS EQUIPMENT SPECIALISTS

UPPER NORTH ISLAND Mobile: 021 999 768

LOWER NORTH ISLAND & SOUTH ISLAND Mobile: 021 456 418

CONCRETE SPECIALISTS

UPPER NORTH ISLAND Mobile: 021 501 143 Mobile: 021 532 219

LOWER NORTH ISLAND Mobile: 021 610 838

SOUTH ISLAND Mobile: 021 877 384

UNG/MAN HIANZ PRINCIPAL SPONSORS 2010 - 2021

CONSTRUCTION & GENERAL SALES

AUCKLAND/NORTHLAND Mobile: 021 977 324

AUCKLAND Mobile: 021 616 875

WAIKATO, BAY OF PLENTY Mobile: 021 725 169

WELLINGTON/LOWER NORTH ISLAND Mobile: 021 729 005

CHRISTCHURCH NORTH Mobile: 021 503 683

CHRISTCHURCH SOUTH Mobile: 021 405 180

AUCKLAND HEAD OFFICE

6-10 Parkway Drive, Mairangi Bay, Auckland 0632 PO Box 100-040, North Shore City 0745 Phone: (+64) 09 443 2436 Email: sales@yrco.co.nz

WELLINGTON BRANCH

8 Broken Hill Road, Kenepuru Porirua 5022 Phone: (+64) 04 212 2456 Email: saleswell@yrco.co.nz

CHRISTCHURCH BRANCH

20 Nga Mahi Road, Sockburn. Christchurch 8042 Phone: (+64) 03 341 6923 Email: saleschch@yrco.co.nz

DIGGER & EARTHMOVING SPECIALISTS

UPPER NORTH ISLAND Mobile: 021 820 096

LOWER NORTH ISLAND Mobile: 021 630 701

CHRISTCHURCH NORTH Mobile: 021 503 683

CHRISTCHURCH SOUTH Mobile: 021 405 180

NATIONAL SALES MANAGER Mobile: 021 708 099



Compaction 4-6
Earthmoving7-8
Waterblasters9
Access Equipment10
Material & Glass Handling11
Access Equipment12
Pumps13-15
Generators16
Compressors, Engines & Industrial17
Concreting Equipment 18-20
Lighting Towers & Dust Suppression21
Concrete Cutting & Drilling
Surface Preparation24-25
Outdoor Products & Landscaping26
Outdoor Products27



Youngman Richardson & Co Ltd is a fully New Zealand owned private company that has been serving the construction, hire and agricultural industries for over 39 years with a customer base throughout New Zealand. We have a reputation for **Quality, Service** and **Ethics**. We pride ourselves on our commitment to customers, product knowledge and expertise with a spare parts service that's "the best in the business".





PROUD TO BE 100% NEW ZEALAND OWNED & OPERATED

YRCO.CO.NZ





- Cloud-based GPS tracking software
- Check asset locations
- Scheduled & automated service alerts
- Pair with mobile & on-site servicing
- Protect against theft
- Multi-device compatible PC + Mobile App





Multi-device access

> Asset location finder

Cloud-based asset monitoring & management



Mobile servicing



Anti-theft

Automated service reminders









TG45S 430kg Weight 680kg Drum (mm) 355Dia 650W Weight Drum (mm) 550Dia 750W Cent. force 12.5kN Honda GX270 9hp Petrol

MRH-700GS

Cent. force 10.8kN Honda GX390 13hp 10.8kN



COMPACTION

Mikasa Reversible Plate Compactors Ideally suited for civil

engineering, construction and drainage contractors as well as the hire industry. They offer a high compaction capacity, travel speed and feature a full hydraulic reversing mechanism.



2



POSITIVE THROTTLE ENGAGEMENT Exclusively on diesel machines. Guarantees full throttle operation and maxmum compaction by eliminating midpoint RPM.

Hourmeter - allows accurate tracking of

- displays engine RPM while in operation.

NFW

hours and maintenance intervals. Tachometer



EASY SERVICE Serviceability with easy access to all maintenance points.

OPTIONAL FEATURE:



COMPACTION METER

The new Mikasa 'Compass' compaction meter is a measuring and display system for continuous compaction control - located in clear view of the operator. Available on 308,408 & 508 Models.

NEW



MVHR60H A (Petrol) Weight 68kg Plate (mm) 480x350 Cent. force 15.0kN Honda GX120 4hp Start Recoil

YEAR WARRANTY

2 Year (24 Months) Warranty* on Mikasa

& HATZ Engines based on service & maintenance contract. * Conditions apply.



DIGITAL DISPLAY

MVH128GH (Petrol) Weight 122kg Plate (mm) 590×400 Cent. force 23.5kN Honda GX160 5.0hp Start Recoil



MVH158GH (Petrol)Weight148kgPlate (mm)700×430Cent. force27.0kNHonda GX2006.5hpStartRecoil



WVH208 Series (Petrol or Diesel)Weight240kgPlate (mm)720X500Cent. force37.0kNHatz6.7hpStartElectric/Recoil



MVH308 Series (Petrol or Diesel)Weight325/360kgPlate (mm)860x445/600Cent. force45.0kNHatz9.0hpStartElectric/Recoil



 MVH408 Series (Diesel)

 Weight
 423kg

 Plate (mm)
 900x500/650

 Cent. force
 55.0kN

 Hatz
 9.0hp Diesel

 Start
 Electric/Recoil



 MVH508 Series (Diesel)

 Weight
 536kg

 Plate (mm)
 900x500/650

 Cent. force
 65.0kN

 Hatz
 11.9hp Diesel

 Start
 Electric/Recoil

COMPACTION



ARX23-2 / ARX26-2 ARX40-2 / ARX45-2 Working Width 1000 - 1380





ARX16K / ARX23-2C / ARX26-2C ARX40-2C / ARX45-2C Working Width 900 - 1380mm Operation Weight 1450 - 4320kg

Light Tandem Articulated Vibratory Roller

Ammann tandem rollers in the 1-4.5 tonne class offer full-flush compaction both sides of the machine, double drive front and rear as well as double vibration at front and rear. The dash-2 series of light tandem rollers features a quick drum adjustment from offset to in-line configurations. Rollers that are offset are able to work close to obstructions.

Heavy Articultated Tandem Roller

Ammann ARX tandem rollers were developed to meet the demand of today's road building projects worldwide to compact asphalt sub-layers and wearing courses as well as gravel and soil. The unique design reflects the combination of high-performance compaction as well as operator-safety and comfort.



AV70X / ARX90 / ARX110 / ARX130 Working Width 1450 - 2100mm Operation Weight 7365 - 13030kg

Heavy Single Drum Roller 7-22t

The extraordinary safety, excellent compaction performance and modern design of heavy-weight Single Drum Rollers guarantee high efficiency and best results even under the toughest working conditions.

ARS70 / ARS110 / ARS130 ARS150 / ARS170 / ARS200 ARS220

Working Width 1680 - 2240mm Operation Weight 6490 - 26060kg







controlled

ARR 1575 Working Width 640 - 850mm Operation Weight Max 1450kg Remote Controlled



Rammax Trench Rollers

The articulated trench rollers produced by Rammax are developed for various applications on heavy terrains. Can navigate around manholes without difficult steering.

Ammann ARR 1575 Trench Roller has an optional extra intelligent compaction system.

The system, ACEecon, eliminates guesswork by measuring compaction progress in real time. The information is communicated to the operator via an LED display on top of the machine.

Infra-red remote control – machine automatically stops without direct visibility, automatically stops outside 2-20M.

Paver

The AFW150-2 is a unique machine that has no competitors in the market. The tight turning radius and clearance width make it ideal for paving footpaths and handling repair work in narrow surroundings. The paver is easy to transport and allows a fast set-up on the jobsite.



ART280

Ammann's new tyred roller features a new cab and a unique ballasting system that can be quickly and significantly adjusted.





EARTHMOVING

Mini Excavators Reliability, greater visibility, lower noise levels and ease of operation are key benefits of the KATO Mini excavator range.



HD12VXE Operating Weight Max Digging Force Engine



HD17VXE Operating Weight Max Digging Force Engine



1690kg 15.7kN (1600kgf) YANMAR 3TNV70



HD19VXT 1745kg 15.7kN (1600kgf) Operating Weight Max Digging Force YANMAR 3TNV70



HD19VXT Cabin Operating Weight Max Digging Force Engine

1905kg 15.7kN (1600kgf) YANMAR 3TNV70



HD25V4 Operating Weight 2555kg 19.6kN (2000kgf) Max Digging Force KUBOTA D1305 Engine Options - Cabin or Rops Canopy



HD30V4 Operating Weight 3105kg 29.1kN (2970kgf) Max Digging Force Engine YANMAR 3TNV88 Options -Cabin or Rops Canopy - Steel or Rubber Tracks



HD35V4 Operating Weight 3525kg 29.1kN (2970kgf) Max Digging Force Engine YANMAR 3TNV88 Options - Cabin or Rops Canopy - Steel or Rubber Tracks



HD45V4 Operating Weight 4855kg 31.0kN (3160kgf) KUBOTA V2403-DI Max Digging Force Engine Options - Cabin or Rops Canopy - Steel or Rubber Tracks



HD55V4

Operating Weight Max Digging Force Engine Options - Cabin or Rops Canopy







5575ka

HD60V4 Operating Weight Max Digging Force

41.2kN (4800kgf) KUBOTA V2403-DI Engine Options - Cabin or Rops Canopy - Steel or Rubber Tracks

HD85V4 Operating Weight Max Digging Force Engine Options - Cabin or Rops Canopy - Steel or Rubber Tracks

8440ka 55kN (5608kgf) YANMAR 4TNV98C

Hydraulic Breakers and Accessories

Fine silenced "X" series and close type hydraulic breakers. Fine number 1X - 23X Weight 120kg - 1760kg Suits Excavator 0.8-1.5 Tonnes - 22.0-28.0 Tonnes





FINE 3X 145kg Weight

EARTHMOVING



Kato Mini Dumpers:

KATO Tracked Dumpers are ideal for transporting and moving various kinds of materials around the work yard and in places that are difficult to access.



CARRY 105 Capacity Unit Weight 500KG 290 Kg Honda GX200 6.5Hp



CARRY 107.HT Capacity 700KG Capacity 700KG Unit Weight 615 Kg Honda GX390 13.0Hp



CARRY 105.LS 500KG Capacity Unit Weight 345 Kg Honda GX200 6.5Hp C/w Loading shovel



CARRY 107.HTLS 700KG Capacity 700KG Unit Weight 665 Kg Honda GX390 13.0Hp C/w Loading shovel



CARRY 105EL 400KG Capacity 400KG Unit Weight 375 Kg Electric fast charge



CARRY 110 1000KG Capacity Unit Weight 930 Kg Yanmar Water Cooled 14kW

Tuffbelt Portable Conveyor:

Tuffbelt mini-maxi conveyor belts are excellent for hire equipment for builders, landscapers, renovation firms and development or demolition contractors. Ideal for transporting building materials and especially handy for areas with narrow access.

TUFMTB45



Tuffruk Mini Dumpers:

Tufftruk Wheeled Dumpers are very compact 4x4 mini dumpers with an articulated chassis to navigate bends and corners with ease.





WATERBLASTERS

YRCO Pro Series Waterblasters - Petrol



YR2700AR Pressure 2200psi Max flow 11 L/min Honda GX160 5hp



YR3000AR Pressure 2600psi Max flow 13.5 L/min Honda GX200 6.5hp




YR3500AR.HR Pressure 3000psi Max flow 15.5 L/min Honda GX270 9hp



YR4000AR.HR Pressure 3700psi Max flow 17.5 L/min Honda GX390 13hp

Pneumatic tyres. 14m of hose & gun.



Fitted with Annovi Reverberi high pressure pumps



ELECTRIC START OPTION YR4000ARE Pressure 3700psi Max flow 1175 L/min Honda GX390 13Hp Electric Start

Dual Pressure Washer





DCP-2200 Weight: 33kg Pressure: 2200psi Rotary Size: 450mm Honda GX200 6.5hp

DPW-2500Weight66kgPressure2500psi (max)Rotary Size530mmHonda GX2UO6.5hp



DPW-4000Weight107kgPressure4000psi (max)Rotary Size610mmHonda GX39013.0hp

Choose your Engine and pressure options below:



Honda GX390 Recoil start Pressure 3700psi Max flow 17 L/min *High pressure hose reel only



Honda IGX390 Electric start Pressure 3000psi Max flow 21 L/min



Honda IGX390 Electric start Pressure 3700psi Max flow 17 L/min



Engine: Honda IGX690 Electric start Pressure 4000psi Max flow 21 L/min

Engine: Kohler KD625.2 Diesel Electric start Pressure 3000psi Max flow 30 L/min

Trailerised

YRCO trailerised water blasters are available in a numbers of configurations.

500 Litre single axle fully galvanised trailer with low water cut-out. Match up with one of 4 different engine options.

1000 Litre double axle fully galvanised, braked trailer with low water cut-out. Match up with one of 4 different engine options.





ACCESS EQUIPMENT



Electric Runabouts

Self-propelled. Compact design and great manoeuvrability. Simple operation.

Model:	GRC12
Working height (max)	5.66m
Lift capacity (max)	227kg
Power	24V
Weight	950kg

GR15GR206.47m8.02m227kg159kg4 x batteries, 6V1026kg1148kg



Telescopic Booms

The ultimate in reach and range. Fast set-up and state-of-the-art features.

Model:	S-45XC	S-65TRAX	S-65XC
Working height	15.56m	21.8m	21.81m
Lift capacity	300/454kg	227kg	300/454kg
Power (Diesel)	48hp	48hp	Electric/Diesel
Weight	7282kg	12,519kg	11,673kg
Model:	S-85XC	SX-125XC	SX-135XC
Working height	27.91m	40.1m	43.15
Lift capacity	300/454kg	300/454kg	300/454kg
Power (Diesel)	74hp	74hp	74hp
Weight	18,126kg	20,700kg	21,636kg
Model:	SX-150	SX-180	
Working height	48.33	56.89m	
Lift capacity	340kg	340kg	
Power (Diesel)	74hp	74hp	
Weight	2,613kg	25,108kg	

Articulating Booms

Self-propelled. Smaller models for tight access, up to large models with extended reach and jib options.

Model:	Z30/20NRJ	Z33/18	Z34/22N	
Working height	10.89m	12m	12.52m	
Lift capacity	227kg	200kg	227kg	
Power	Electric	Electric	Electric	
Weight	6622kg	3665kg	5216kg	
Model:	Z34/22IC	Z40/23RJ	Z45XC	
Working height	12.62m	14.32m	15.56	
Lift capacity	227kg	227kg	300/454kg	
Power	Electric	Electric	Electric	
Weight	4854kg	6940kg	7530kg	
Model: Working height Lift capacity Power Weight	Z45/25JRT 15.86m 227kg Electric/Diesel4 6134kg	17.59m 227kg	JRT 260/37FE 20.16M 227 Electric/Diese 7686kg	-
Model:	Z62/40	Z80/60	ZX135/70	-5-
Working height	20.87m	25.77m	43.15m	
Lift capacity	227kg	227kg	272kg	
Power (Diesel)	48hp	78hp	74hp	
Weight	10,886kg	17,010kg	20,267kg	

Trailer Mounted Booms

Easy to tow and set up. Hydraulic outriggers with automatic levelling system.

Model: Working height Lift capacity Power Weight

TZ34/20 ight 12.36m y 200kg DC Electric 1450kg

TZ50 17.1m 200kg ic DC Electric/Petrol 2200kg



Electric Scissors

Nothing beats a Genie scissor lift for performance and safety.

Model:	GS1330	GS1532	GS1932
Working height (max)	5.9	6.57m	7.8m
Lift capacity (max)	227kg	272kg	227kg
Power	Electric	Electric	Electric
Weight	885kg	1238kg	1500kg
Model:	GS2032	GS2632	GS3232
Working height (max)	8.1m	9.92m	11.75m
Lift capacity (max)	363kg	227kg	227kg
Power	Electric	Electric	Electric
Weight	2027kg	1956kg	2352kg
Model:	GS2046	GS2646	
Working height (max)	8.1m	9.92m	
Lift capacity (max)	544kg	454kg	
Power	Electric	Electric	
Weight	1974kg	2447kg	
Model:	GS3246	GS4047	
Working height (max)	11.75m	13.7m	
Lift capacity (max)	318kg	350kg	
Power	Electric	Electric	
Weight	2812kg	3222kg	



Rough Terrain Scissors

Superior gradeability, traction control and standard 4WD for diesel models.

DIESEL							
Model: Working height Lift capacity Power (Diesel) Weight	GS2669 9.70m 680kg 24.8hp 3739kg		GS33 11.75m 454kg 24.8h 3921k	þ	GS3 12.00 1134 49h 6743	kg p	
Model: Working height Lift capacity Power (Diesel) Weight	GS4069 14.12m 363kg 24.8hp 5078kg		GS43 15.11m 680kg 48hp 6934l	9	18. 68 48	390RTO I5m Okg Ihp 76kg	
ELECTRIC							
Model: Working height Lift capacity (m Weight		GS26 9.7m 680k 4146		GS336 11.75m 454kg 4028kg		GS4069 14.2m 363kg 5371kg	BE



Model:	GS2669DC	GS3369DC	GS4069DC
Working height (max)	9.7m	11.75m	14.2m
Lift capacity (max)	680kg	454kg	363kg
Weight	4002kg	3885kg	5329kg





Super Hoist

A one piece platform that is portable and compact lifting to 3.8m at 136kg and 5.6m at 113kg.

GH3.8	GH5.6
3.8m	5.6m
136kg	113kg
CO ₂	CO ₂
34kg	37kg
	3.8m 136kg CO2

6

Superlift Advantage

A heavy duty design with a patented telescopic mast system. Can lift from 3.49m to 7.94m and 295kg to 454kg.

Model:	SLA10	SLA15
Working height	3.49m	4.98m
Lift capacity	454kg	363kg
Weight	118kg	151kg
Model:	SLA20	SLA25
Working height	6.46m	7.94m
Lift capacity	363kg	295kg
Weight	184kg	204kg

Superlift Contractor

A heavy duty design with interchangeable load handling attachments. Can lift up to 3.94m at 295kg and 7.32m at 295kg.

Model:	SLC12	SLC18	SLC24
Working height	3.94m	5.64m	7.32m
Lift capacity	295kg	295kg	295kg
Power	Manual	Manual	Manual
Weight	102kg	139kg	157kg

AWP Work Platforms

Ideal for high ceiling lighting and general maintenance duties. Can work at height from 8.12m - 14.29m.

Model:	AWP20ACS	AWP25ACS	AWP30ACS
Working height	8.12m	9.57m	11m
Platform height	6.12m	7.57m	9m
Lift capacity	159kg	159kg	159kg
Power (Battery)	12V	12V	12V
Weight	307kg	330kg	352kg

Model:	AWP36ACS	AWP40
Working height	13.1m	14.29m
Platform height	11.1m	12.29m
Lift capacity	159kg	136kg
Power (Battery)	12V	12V
Weight	461kg	472kg

DACS

Material Lifts

A counterbalance weight system capable of lifting weights over obstacles and directly up against walls.

Working height3.06m3.56mLift capacity181kg159kgPower (winch)-reversibleWeight66kg68kg	4.2m 159kg e standard - 70kg
---	---------------------------------------









Wienold Lifts - GML800

Powered by AC 240 volts, DC with battery packs or a manual winch. Up to 900kg to be lifted up to 3.5m or up to 800kg to a height of 7.9m.

12V

- Model: AC SERIES Lift height 7.90m 800kg Lift capacity Elec Winch Powe Weight 352kg
- DC SERIES M SERIES 7.90m 7.90m 800kg 800kg Manual .352ka 316kg



SLK Series

A counterbalance weight system capable of lifting weights over obstacles and directly up against walls. Can lift up to 450kg to 2m or 300kg up to 7.9m.

Model:	SLK5	SLK10	SLK15	
Lift height	2.0m	3.50m	5m	
Lift capacity	450kg	450kg	360kg	
Weight	98kg	118kg	144kg	1
Counterbalance	128kg	128kg	128kg	

SLK25

300ka

204kg

128ka

7.9m

Model: SLK20 Lift height 6.5m 360kg Lift capacity Weight 184kg Counterbalance 128ka

Mo Lift

l ift

We

Model:

Lift height

Lift capacity Weight





WLU Premium

Smaller more compact Wienold Material lift is suitable for tighter sites where larger space is an issue. The chassis is made from solid steel. Max lift height on the WLU/K5P is 5.15m with a capacity of 360kg.

del:	WLU/K1.7	WLU/K2.8
: height	1.7m	2.85m
: capacity	400kg	400kg
ight	97kg	113kg

4.0m

400ka

129ka

WLU/K4 360kg

WLU/K5.1 145ka

Mini Floor Crane

Classic counterweight with two long, rear-facing arms with counterweights. 900 kg static and 750 kg dynamic payload, which are brought to a hook height of 2.90m.

Model: 750 Lift height Lift capacity 2.9m 750kg Weight 490ka

Powered Hand Truck

A universal materials handling solution for one person to lift up to 140kgs.

> PHT150 Lift Height Lift Capacity 300mm-1900mm 140kg 44kg weight







ACCESS EQUIPMENT





Athena HE-Line

The HE-Line range of tracked scissor lifts is capable of max working height 7.82-14m with a maximum capacity of up to 300kg.

Model:

Engine

Weight

Model:

Engine Weight

Model:

Engine Weight

Lift capacity

Working height

Lift capacity

Working height

Lift capacity

1470-HE-EVO 14.0m 300kg Kubota Z602 3420 Kg

Athena BL-Line

The range of Building Line reaches between 7.9-10m with a maximum capacity of up to 300kg. EVO models can self-level while raised and move at height. There are also Bi-energy options.

Model: 850-BL* Working height Lift capacity 7.9m 250kg Honda 13HP & Electric 240V Engine Weight 1781 Kg

Model: 850-BL-EVO Working height Lift capacity 7.9m 250kg Diesel 11HP & Electric 240V Engine Weight 2200 Kg

870-BL-EVO Working height 7.9m 250kg Diesel 11HP & Electric 240V 2460 Kg

> 1090-BL-EVO* 10.0m 300kg

Diesel 11HP & Electric 240V 2830 Kg

*Bi energy option available

Spider Lifts

Ideal for hard to reach places, lightweight and duel energy platform spiders will virtually go anywhere. Engine powered and electric.



Model: 13.80 Weight 1760kg Working Height 12.99m



Model: 22.10 Weight 2980kg Working Height 21.7m



Model: 15.75 Weight 2060kg Working Height 15m



Model: 27.14 Weight 5000kg Working Height 27.0m



Model: 18.90 Weight 2457ka Working Height 17.6m



Model: 33.15 Weight 6980kg Working Height 32.4m

12



The JT-Line tracked self-propelled telescopic boom has +/- 150 longitudinal and lateral levelling. This unit also has an active dynamic bi-levelling chassis.

Model: JIBBI-1250-EVO Working height 12.2m 230kg Lift capacity Diesel 19.2 HP Engine Weight 2850 Kg

JIBBI-1670-EVO Working height 16m 230kg Lift capacity Diesel 19.2 HP 3850 Kg







Model:

Engine Weight

Multi-Loaders are a range of tracked loader with Bi-Levelling technology capable of transporting up to 2,500kg on slopes equal to 20º.

Model: Lift capacity Engine Weight

MULTI LOADER 2500kg Electric 240V 1800 Kg



Jack Booms

Self propelled or stabiliser jacks to level machine on uneven ground.

Model: Working height Lift capacity Power (Diesel) Weight

ATN ZEBRA 16RT 16.8m 230kg 35hp 8050kg





Weight 2800kg Working Height 19.4m



Model: RR14 EVO3 Rail Boom Weight 13400kg Working Height 14.4m









Our range of portable clean water pumps, trash pumps, diaphragm pumps and flexi-drive pumps have been manufactured to be user-friendly and portable. Water pumps we stock are durable, reliable, and made with quality components for New Zealand's tough working conditions, and are ideal as portable water pumps for contractors and hire companies.

DAISHIN.

Clean Water

General all-purpose pumps. Sizes 1"(25mm), 2" (50mm), 3" (75mm) and 4" (100mm). Petrol and diesel models available.



SEH-25L 1" (25mm)

Max flow 115 L/min Total head 32m





SEH-40H1 " (40mm) Max flow 280L/min Total head 43M

N SEH50X 2"(50mm) Max flow 640 L/min Total head 27m



SCR-80YD Diesel Powered Pump 3" Clean Water 900 L/min 28, Head Yanmar Diesel Engine



SEH8OX 3"(75mm) Max flow 1100 L/min Total head 27m



SE100XD Diesel Powered Pump 4" Clean Water 1100 L/min 24m Head Subaru Diesel Engine

Semi-Trash For solids up to 20mm diameter. Petrol and diesel models.



SCR-50YD Diesel Powered Pump

an Water 550 L/mir

32, Head Yanmar Diesel Engine

STH-50X 2"(50mm) Max flow 600 L/min Total head 29m



STH-80X 3"(75mm) Max flow 900 L/min Total head 26m

Full-Trash For solids 20mm up to 35mm. Petrol and diesel models.



KTH-50X 2"(50mm) Max flow 700 L/min Total head 30m



KTH-80X 3"(75mm) Max flow 1340 L/min Total head 27m



KTH-100X 4"(100mm) Max flow 900 L/min Total head 26m



SWT-50YD Diesel Powered Pump 2" Trash 550 L/min Total head 24m

High-Head For sprinklers & firefighting and water transfer to high places.



SERH50 Max flow 431 L/min Total head 80m

Diaphragm Self-priming. Can be run dry.



KDP-50X 2"(50mm) Max flow 197 L/min Total head 7.6m



KDP-80X 3"(75mm) Max flow 333 L/min Total head 7.6m

Pump Accessories

Suction & layflat hose, 'Camlock' fittings, PVC strainer and hose couplings.





SCR-80YD Diesel Powered Pump 3" Clean Water 1150 L/min Total head 27m

PUMPS









Submersibles Electric

Suitable for construction sites, underground utility maintenance, light industrial, farm and horticulture, landscaping and flood dewatering uses.



PXL52522 1"(25mm) Max flow 120 L/min Total head 10m Single phase



P315W Max flow 690 L/min Total head 17m Single phase



PQ55022 2"(50mm) Max flow 220 L/min Total head 11m Single phase



P322D Max flow 700 L/min Total head 23m Three phase 2.2 kW

Flexidrive Submersibles

Ideal for construction sites. Petrol & diesel models. Standard flexidrive shaft length 7m.



Pump and drive unit sold separately

MIKASA

Drive Unit: GE5L (Petrol)

Flexible Drive Pump: WP2L 2"(50mm)Max flow500 L/minTotal head13m

 Flexible Drive Pump: WP3LB 3"(75mm)

 Max flow
 1200 L/min

 Total head
 23.1m

FLEXTOOL Drive Unit: Petrol GX160 3 Dog Drive

Flexible Drive Pump: 2" FT20180Max flow1050 L/minTotal head26.0m



PBX7-55022 2"(50mm) Max flow 330 L/min Total head 15m Single phase



P437D Max flow 1400 L/min Total head 18.5m Three phase 3.7 kW



P455D Max flow 1900 L/min Total head 23m Three phase 5.5 kW

Koshin Portable Sprayer

For a wide range of hand-held spraying jobs. Petrol powered.



Model KVER100Max flow8.6 L/minSpray coverage2-2.5m

Drive Unit: Petrol GX160 3 Dog Drive Flexible Drive Pump: 2" FT201801 Max Flow 1050 L/min Total head 26.0m



Selwood Pumps











FEATURES

- Solids handling to 100mm
- Indefinite dry running
- Vortex style pump
- Environmentally friendly Selprime automatic self priming
- Emission compliant engines
- Ease of operation & maintenance
- Proven design

FEATURES

- Flows up to 600 m³/h
- Indefinite dry running
- Environmentally friendly Selprime automatic self priming
- Emission compliant engines
- Ease of operation & maintenance
- Robust construction

FEATURES

- Total heads up to 158m
- Mechanical shaft sealing • Environmentally friendly Selprime automatic self priming
- HM hard metal pumps for abrasive applications
- Emission compliant engines • Ease of operation &
- maintenance
- Robust construction

FEATURES

- 50mm, 75mm and 100mm models available
- Non turbulent flow
- Viscous liquids
- Dry running
- Choice of materials

FEATURES

- 75mm
- Non turbulent flow
- Viscous liquids
- Dry running
- Choice of materials

Selwood Solids Handling 'S'Range

Specification		S100	S150	S200	\$300
Capacity	m³∕h	165	320	635	1290
Total Head	m	21.3	21.3	29	27
Solids Size	mm	75	100	100	100
Inlet / Outlet	mm	100	150	200	300

APPLICATIONS

- Raw & screened sewage
- Sludge / Slurry

Water with fine & large solids

• Water with rags & fibres

Selwood Drainer 'D' Range

Specification		D75	D80	D100	D150	D150W	P D150R	D200
Capacity	m³/h	59	90	120	380	275	315	600
Total Head	m	23.5	23	26	40.5	21	27	37.5
Solids Size	mm	29	29	29	45	45	45	55
Inlet / Outlet	mm	75	80	100	150	150	150	200

APPLICATIONS

- Clean water
- Water with fine solids
- Water with larger solids
- Screened sewage

Selwood High Head 'H' Range Cussifiesticu 11100 11125 11150 11200

Specification		H80	HIUU	HI25	H150	H200
Capacity	m³/h	95	225	TBA	450	750
Total Head	m	95	120	TBA	114	158
Solids Size	mm	19	30	TBA	30	45
Inlet / Outlet	mm	80	100	ТВА	150	200

APPLICATIONS

- High head dewatering
- Pipeline testing & cleaning
- Water boosting

Selwood PD75

Specification		PD75
Capacity	m³∕h	30
Total Head	m	30.5
Solids Size	mm	6
Inlet / Outlet	mm	75

A

Selwood PD75E Electric Option

Specification		PD75E
Capacity	m³∕h	30
Total Head	m	30.5
Solids Size	mm	6
Inlet / Outlet	mm	75
Total Head Solids Size	m mm	30.5 6

APPLICATIONS

- Light and heavy oils
- Sludge / Slurry
- C/W 3 Phase kW motor
- Water with fine solids
- Petroleum industry products

Data Sheets are available at www.selwoodpumps.com

15

- Water with fine solids

- Petroleum industry products

High volume jetting

• Temporary fire pump



APPLICATIONS
 Light and heavy oils
• Sludge / Slurry

GENERATORS



YRPRO Series Petrol 2.4kVA to 11kVA. 3-phase model 12kVA.

Options: base plate, roll bar frame & pneumatic wheels. Diesel version available.



A1BFX / A1CFX Max Output 2700W/3300W Cont Output 2500W / 3000W



M1RW Max Output 5500W Cont Output 5000W

Welder/Generator

General arc welding, maintenance and farm use. DC battery charging facility.

Comes complete with welding cables, earth clamp, hand piece and helmet.

ASI 200 Generator capacity 7kVA Weld capacity 200amps Weight 97kg



A1DFX Max Output 4500W Cont Output 4100W



SE20 Max Output 7700W Cont Output 7000W



Inverter Type - Super Silent



YRG2400I Max Output 2400W Cont Output 2100W



EU10IS Max Output 1000W Cont Output 900W



EU22I Max Output 2200W Cont Output 1800W



SINGLE PHASE

DA-6000SS Max Output 6.0kVA Cont Output 5.5kVA DCA-10ESXDA Max Output 8.8kVA Cont Output 8.0kVA DCA-25SPXDA Max Output 22.0kV Cont Output 20.0kVA

16



EU70IS Max Output 7000W Cont Output 5500W

THREE-PHASE

DCA-13ESKDA Max Output 11.5kVA Cont Output 10.5kVA DCA-25ESKDA Max Output 22.0kVA Cont Output 20.0kVA DCA-35SPKDA Max Output 31.5kVA Cont Output 30.0kVA DCA-45SPI Max Output 38.9kVA Cont Output 37.0kVA DCA-60USH2

Max Output 55.0kVA Cont Output 50.0kVA



All YRPRO Series Generators include an RCD (earth leakage and circut breaker) option.



SE20E40.3PH.HATZ Max Output 7600W Cont Output 6200W






32 AMP Single Phase

WELDER /GENERATOR Soundproof, superior arc performance.



Generator 10kVA/15kVA Weld amps 300/400 Weight 384kg/460kg





• Easy starting and quick response

Denyo Soundproof

- Weatherproof canopy
- Three phase models suitable for building sites, outdoor events and standby/emergency





Generator capacity - 7kVA Weld capacity - 200amps Compressor - 12 CFM Twin Cylinder Battery charge Weight - 165kg

4 in 1 Work Station

PRO

Max Output 5500W

Cont Output 5000W

PRO

SE20E40W.WS.HATZ

Max Output 7700W

Cont Output 7000W

M1R







COMPRESSORS, ENGINES & INDUSTRIAL

Petrol and Diesel Generators









MKX-6 (Petrol) Max Output 5800W Rated Output 4600W

MKX-10 (Petrol) Max Output 8000W Rated Output 6400W

MKX-16 (Petrol) Max Output 14000W Rated Output 12800W

MKX-23 (Petrol) Max Output 19000W Rated Output 18000W

Electric and Hydraulic Breakers

Jackhammer Trolley JHT 27.5kg Suits most 16Kg Jack hammers



Hydraulic Power Packs Petrol model shown



BH051 Finishing 5.5kg BH163 Gen purpose 16kg BH112V Light work 11kg BH23K32EV High power 21.5kg

Heaters

Shizuoka radiant infra-red, diesel and electric heaters. Suitable for indoor/outdoor use.



DCP-2200 Weight: 33kg Pressure: 2200psi Rotary Size: 450mm Honda GX200 6.5hp

NEW

DPW-2500 Weight: 66kg Pressure: 2500psi (max) Rotary Size: 530mm Honda GX200 6.5hp



Dual Pressure Washer

DPW-4000 Weight: 107kg Pressure: 4000psi (max) Rotary Size: 610mm Honda GX390 13.0hp

Mobile Charging Pod

Mobile powered cabinet to safely store power tool batteries and chargers while charging batteries.



Size (WxDxH): 1480 x 430 x 1370mm Weight: 74kg Locker Dimensions (WxDxH): 580 x 330 x 370mm

Biemmedue radiant heaters and space heaters



VAL6.EPX1 Heat 140,000Bthu/hr Power 230V single phase Weight 50kg



VAL6.KBE1S Heat 112,000Bthu/hr Power 230V single phase Weight 38kg



VAL6.FIR2000 Diesel fuel infrared heat clean exhaust (OPPM) 24hr run time / 4.5 Tank





Heat 174,000Btu/hr Power Electrical 230V or 110V single phase Weight 81Kg

EC55

Floor sanders

ESSEX-SILVER-LINE

Dehumidifiers





DR190 230V/50HZ Motor Weight 55kg

DR310 230V/50HZ Motor Weight 76kg

Hatz Industrial Engines

These heavy-duty diesel engines are economical, robust, reliable and low noise. Safe starting even at extremely low temperatures.

Air-cooled, single and multi-cylinder 2.8kW to 48kW. Some models feature 'Silent Pack' sound proofing for extra quiet use.

17









SL7 Edger 180mm Disc pad Disc speed 3600rpm 13.5kg Weight

SL8 Drum Sander 200mm Drum Drum speed 1800rpm Weight 55.0kg

FIRE 25 Heat 89,000Bthu/hr Power 230V single phase

Weight 42kg

HATZ

CONCRETING EQUIPMENT



Ride-On Power Trowels

Ideal for finishing large commercial jobs. Well balanced with a low centre of gravity for stability. Pneumatic tyred transport kit. Mechanical & Hydrostatic available.

HHNG5 Mechania Trowels Width Petrol Weight	cal Dual 5 2330mm 35hp 491kg	JWN24 Mechani Trowels Width Petrol Weight	cal Dual 4 1910mm 22hp 356kg	LD6 Hydrostatic Trowels Dual 6 Width 1905mm Diesel 23hp Weight 392kg
нтх6н		STX6H		

Hydrostatic Trowels Width Dual 6 2330mm Diesel 70hp Diesel 1063kg Weight Weight

Hydrostatic Trowels Width Dual 6 2970mm





STX6H

Walk-Behind Power Trowels

55hp

. 1158ka





CA4MLE.GX160 - 24' Width Weight 610mm 57kg Honda GX160 5hp *Edger model

> B46.GX340 - 46" 1170mm 110kg/113kg Width Weight Honda GX340 11hp



J3036H55 - 30"/36' Width Weight 762 / 914mm 81kg Honda GX160 5hp *Edger model

J36.GX160 - 36' Width Weight 914mm 86kg Honda GX160 5hp

нтх6н

HDA48413H - 48"

NEW



Power Pole Finisher

Start finishing even when surface is wet. Pole lengths can be added up to 9.0m (30')



Engine 22cc Trowels 4 at 5° Width 860mm Weight 10.8kg

PPF



Magic Screed

Can level up to 4 times more concrete than traditional method.



HD7070 Engine 35cc, 4-stroke Blade sizes 4', 6', 8',10', 12', 14', 16'

Flextool





Roller Screed

Ideal for pervious concrete, and concrete laying jobs including wide, sloped or circular pours. Adjustable tube sizes.



18







Trowel Blades

Top quality MQ Whiteman replacement blades and pans for your walk-behind or Ride-on trowel. Using high carbon, high performance tool steel allows MQ Whiteman to produce a very durable and long-lasting blade.

FINISH BLADES

for walk-behind and ride-on trowels, versatile, cost effective blade for all applications.

COMBINATION BLADES for walk-behind and ride-on trowels when quick change ability can be a high priority.





C464

F900 F10616

C244

Bull/Channel Floats

Suitable for use with clip together or telescopic handles.

150mm

900mm,

1800mm

Width Length 1200mm.

Concrete Placing Rakes

SPR8180

Light weight concrete placing rakes are ideal for spreading and placing concrete and any other soft landscaping mediums.



Hand Trowels

This range of trowels is produced using high carbon steel to optimise blade flexibility and durability and used for smooth finishing of concrete. Available in ProSoft rubber grip and solid moulded plastic handles.

NEW



Handscreed

Flextool Concrete Screed

This aluminium concrete screed with a level vial comes with a clamp-on style handle.



Available in 6 lengths 1200mm (4') / 1800mm (6') / 2400mm (8') 3000mm (10') / 3600mm (12') / 4200mm (13.3')

Wheelbarrow



Float Pans

NEW

Float pans greatly increase the ability to achieve a flatter floor. Multiquip offers a variety of float pan options ranging from Z-Clip to Latch Pin, Domed (Flat) to Superflat.



Edges

The concrete edger trowel is used to create a smooth edge to slab edges.



Finishing Brooms



Bristle type medium 600mm / 750mm / 900mm Length

Walking Tools

Walking trowels and walking tools enable the operator to trowel concrete in a standing position.



CONCRETING EQUIPMENT AND PRODUCTS





Mortar Mixers

Small and lightweight for mixing

products that come in bags



NEW

MIX-ALL Capacity 56L 220V / 50 HZ Weight: 30kg

Above and below the ground waterproofing products

Fosroc provide a comprehensive range of above and below the ground waterproofing products and systems such as repair mortars, corrosion management, protective coatings and strengthening systems.

YR350R (petrol)

Capacity 350L Honda GX160 5hp

Weight 232kg

Road towable

Concrete Mixers

Petrol & electric, portable & towable models



Petrol & Electric Capacity 3 cu.ft / 85L Weight 62.6kg



YRA302TSB Capacity 100L Honda GX120 4hp Polythylene option: YRA302TPB Electric option

Vibrators Petrol

For footings, foundations & driveways



GE5L Flexible shafts 6m Head size 28, 38, 45 & 70mm Honda GX120 4hp



FT201889-UNIT Engine GX35 35cc Head size 44mm Weight 11kg Flexible shaft 540mm





OZBP50 Back Pack 1.75hp/2.5hp 38mm/63mm 8.6kg/10.9kg



Heavy Duty Lightweight Frame Quick Connect Honda GX35 C/w 2m/3m Shaft and 33mm/44mm steel head



Multiquip Electric

For medium to high-slump concrete.



CV-2B Motor 2.0hp CV-3B Motor 3.0hp

Shaft lengths 1.0m, 2.1m, 4.3m, 6.4m Heads (dia-mm) 35, 43, 54, 67

Vibrators Electric Mikasa MGX Series

Double insulated



MGX32.2

Shaft 2m

Head 32mm

MGX28.1 Shaft 784mm Head 28mm



OZ3.2 Motor 3.25hp

YRCO 'Oztec' Electric Series Lightweight. Adjustable shoulder strap.



Shaft lengths 1m, 1.8m, 2.15m, 3.0m, 4.3m, 6.4m Steel heads (dia-mm) 20, 25, 30, 38, 45, 50, 62 Rubber heads (dia-mm) 50, 70



MIX80 Capacity 80L 220V / 1kw Weight: 106kg

NEW



NEW

Capacity 120L 220V / 1.4kw Weight: 130kg



MIX120



20






Environmentally

friendly

Trailerised

Italian designed and manufactured. Portable and stationary models available. Strong and compact structure with stainless





CUBE+ HYBRID Max height Floodlights up to 8.4M 4 x LED Dry weight 1180kg Lift system Hvdraulic Wind stability up to 80km/h Engine Cooling Air Cooled Total run time 342h

CUBE+ NEXT

Max height Floodlights up to 8.4M 4 x LED Dry weight Lift system 1260kg Hydraulic Wind stability up to 80km/h





DF15000

15.0kW, 3-phase 40 - 50m

43L/min@10 bar

DF Smart

5.8L/min@1 bar

2.2kW

13m

worksites that span long distances.

LINKLITE Max height Floodlights 2.8m 1x30W Weight 8kg Can be linked together



LINKLITE stacked

DF Duo Mini

2.6kW

33-83m²

Dust Suppression

DUST FIGHTER

For demolition and quarry sites. Option of an on-board generator Automatic oscillation: Oº to 300º - Remote Control.

Model	DF3000MPT
Motor	3.7kW
Coverage	20m
Water Consumption	6.5L/min

DF5000 5.5kW, 3-phase 20 - 30m 18.3L/min@10 bar DF7500

30 - 40m

7.5kW. 3-phase

34L/min@10 bar







DF SMART



DF DUO MINI

CONCRETE CUTTING / DRILLING

Ô **Husqvarna®**

Power Cutters - Petrol



K535i Battery 1.2kW Blade size 230mm Cut depth 7600 Weight 3.5kg



K770 Engine Blade size 350mm Cut depth 125mm Weight 10kg



Engine Blade size Cut depth Weight

K770.OIL (C/W Oil Guard) K970.MKIII 74cc 3.7kW 350mm 125mm

9.8kg

NEW



Engine Blade size 94cc 4.8kW 350/400mm Cut depth 125/155mm Weight 11.0kg/11.6kg







K1270.16 Engine Blade size 119cc 5.8kW 400mm Cut depth 145mm 13.7kg Weight

K770 Cut-n-Break 74cc 3.7kW Engine 74cc 3.7kW Blade size 230mm (twin) 400mm Cut depth Weight 9.6kg

K970.MKIII Ring Engine 94cc 4.8 Blade size 370mm 94cc 4.8kW Cut depth 270mm 13.8kg Weight

Power Cutters - Petrol



K970 Chain Engine Bar size Cut depth Weight

94cc 4.8kW 350mm 400mm 9.7kg



K970 Rescue 94cc 4.8kW 350mm Engine Blade size Cut depth 125mm Weight 11kg



K1270 Rail Engine Blade size 119cc 5.8kW 400mm Cut depth 145mm 21.1kg Weight

Hvdraulic



K2500 Flow rate Blade size 40L/min 400mm Cut depth 145mm Weight 8.3kg



к3600 Flow rate Blade size 401 /min 370mm Cut depth 270mm 8.3kg Weight

Power Cutters - Electric High Frequency



K4000 Cut-n-Break 230V, 2200W Motor Blade size 230mm (twin) Cut depth 400mm Weight 8.9kg



9.9kg

Weight

K6500 5500W Motor Blade size 400mm Cut depth 155mm Weight 9.8ka



K6500 HF Ring 14" Motor 5500W

Blade size 370mm

Cut depth 270mm

13.1kg

Weight

K6500 HF RING 17"

5500W

425mm

325mm

12.4kg

K6500 Chain 5500W Motor Weight 9.1ka Cut depth 450mm



PP220 PP65 Power 200-480V 200-480V Weight 9.5kg Air Cooled 3 phase or single phase

10.8kg Remote Control 3 phase or single phase

Wall Saws, Wire Saws & Power Packs





WS482 HF (High Frequency) Spindle output 13kW Blade size 600-1600mm Max. cut depth 730mm Weight 28kg

WS440 (High Frequency) Spindle output 20kW

Blade size 600-1200mm Max. cut depth 530mm Weight 25kg

WSC40 Cut depth 400mm No overcuts

CS10 Wire Saw Wire speed Wire length 24m/s 11m Magazine 10m Weight 100kg



CS2512 Wire Saw Wire speed Wire length 20-25m/s 19m Magazine 16m Weight 150kg



WS220 Power Max Cut 6kW 395mm Max Blade 900mm

PP480HF (High Frequency) Use with WS482 HF Power 20kW 23.4kg Weight

H Husqvarna®

CONCRETE CUTTING / DRILLING

Drilling Systems



DM 220 Power 1850W Drill max 150mm Weight 7.5kg



DM 230 Power 1850W Drill max 150mm Weight 7kg

DM 430 Power 3300W Drill max 400mm

Weight 14kg

DM 650HF 3300W Power 6000W Drill max 600mm

Weight 14kg



DMS 240 Power 2400W Drill max 250mm Weight 20.4kg



DS 250

Travel (L) 685mm Drill max 250mm

Weight 16kg



DS 450 Travel (L) 647.7mm Drill max 450mm Weight 23.3kg

VP 200 Vacuum Pump Electric

Self Propelled Road & Floor Saws

An extensive range suitable for large jobs such as airports and highways. Smaller service and repair jobs, floors, driveways, new concrete, old concrete and asphalt.



FS 7000 55kW, 73hp Power Blade size 1000mm Cut depth 410mm Weight 1032kg



FS 5000 35kW, 48hp Power Blade size 650mm Cut depth 374mm Weight 771kg



FS 3500.G 27.5kW, 36.8hp Power Max blade size 750mm Max cut depth 312mm Weight 450kg



FS 524 series 15.5kW, 20.8hp Power Blade size 600mm Cut depth 241mm 239kg Weight

Floor Saws



8.7kW, 11.7hp

FS 400LV series

Blade size 450mm

Cut depth 162mm

99kg

Power

Weight

FS 309 series

Blade size 350mm

53ka

Cut depth 117mm

Power

Weight



6.3kW, 8.4hp

TS 400 F Power 2700W, 230V Blade size 400mm Cut depth 230mm Weight 96ka

Brick Saws

TS 350 E Power Blade size 350mm Cut depth 100mm Weight 92ka

2700W, 230V Power Blade size Cut depth Weight



2200W, 230V 82ka

TS 60 Power 1800W, 230V Blade size 250mm Cut length 700mm Weight 47ka



1000W, 230V Power Blade size 230mm Cut length 730mm Weight 47ka

Husqvarna Soff-Cut Early Entry Saws The best solution to minimise random cracking.



SOFF-CUT 5000 Engine Blade size 20.13kW, 27hp 355mm Cut depth 100mm 225ka Weight



SOFF-CUT 4200 Engine Blade size 17.2kW, 23hp 355mm Cut depth 76mm 257ka Weight



SOFF-CUT 4000 Engine Blade size 15.3kW, 20hp 343mm Cut depth 70mm 191ka Weight



SOFF-CUT 2000e Engine Blade size 6.5kW, 9hp 254mm Cut depth 38mm 144ka Weight



SOFF-CUT 150 Engine Blade size 3.2kW, 4.5hp 152mm Cut depth 30mm 39ka Weight

SURFACE PREPARATION



Grinders Electric powered grinding/polishing machines.



PG830RC NEW 16.5kW Power Width 830mm 3x270mm Discs Weight 652kg



Width

Weight 598kg

Discs

670mm

NEW 3x270mm



PG540 2.2kW Power Width 560mm 3x230mm Discs Weight 169kg



PG450 2.2kW Power Width 450mm 3x180mm Discs Weight 109kg



PG280 2.2kW Power Width 280mm Discs 1x280mm Weight 70kg

Dust Collectors Powerful dust collector units.

S13

Air

A2000

Phase 1pH

Air requirement

1000/2000m³/h

Rated Input 0.75kW

Phase



S11

Air

Phase

A1000

Phase

1pH

Air requirement 500/1000m³/h

Rated Input 0.3kW

1pH

Rated Input 1.2kW

200m³/h

Air Scrubbers

1pH

Rated Input 1.2kW

200m³/h

NEW



\$26 Phase 1pH Δir 400m³/h Rated Input 2.4kW

Pre Separators



C3000 Recommended as a s ipplement to your Hasqvarna d ist extrator S26 and S36.



\$36 Phase 1pH Air 600m³/h Rated Input 3.6kW



T7500 Phase 3pH Air 600m³/h Rated Input 5.5kW



Slurry Collectors



5.75kW

420mbar

DC 6000

Power Vacuum

Weight

Inlet (dia) 75mm 305ka



W70P 200m³/h Rated Input 1.85kW

Three concrete finishes to choose from: **Hiperfloor**



C5500

Recommended as a supplement to your Hasqvarna dust extrator

T7500, T8600, T10000.

Premium finish

A decorative, high-gloss finish for exposed aggregate floors - Applications include showrooms, high-end real estate and areas where the flatness and reflectivity of the floor are a top priority.

Commercial finish

A medium-gloss finish for semi-exposed and low-exposed aggregate floors. Ideal application for retail areas, shop fronts and indoor public spaces. Easy to clean and low maintenance.

Industrial finish

A low-gloss finish customised for industrial floors. Primarily an indoor application targeting large areas such as factory floors, warehouses and department stores.

SURFACE PREPARATION





Grinders Electric powered grinding/polishing machines.



HTC DURATIQ 8 T8/RT8/X8/RX8 Power 12 / 15 kW Width 800mm Power Discs 270mm 3 or 4 disc Weight 499-574kg



HTC DURATIQ 6 T6/RT6/X6/RX6 Power 7.5 kW Width 600mm Discs 230mm 3 or 4 disc Weight 384-441kg



HTC DURATIQ 5 T5 5 hp(4 kw) 3 hp (2.2 kw) Power 2.2 / 4.0 kW Width 515mm Power Discs 230mm : Weight 70-119kg 230mm x 3



HTC 510 Power Width 2 2kW 515mm Discs 3x230 Weight 133kg 3x230mm



Power Width 2 2kW 450m Discs 180mn Weight 109kg 180mm x 3



HTC 400 Power Width 4kW 400m Discs 1 x 400mm Weight 126kg

н



HTC 280 2.2kW Power 2.2kW Width 280mm Discs 1 x 280mm Weight 70kg



HTC D10 Phase 1pH Air 200m³/h Rated Input 1.2kW



HTC D20 Phase 1pH Air 400m³/h Rated Input 2.4kW



HTC D30 Phase 1pH 600m³/h Air Rated Input 3.6kW

Accessories

Husqvarna

Redi Lock



HTC D60 Phase 3pH Air 620m³/h Rated Input 5.5kW

HTC EZ change blocks

Cup wheels



HTC 80 iD II Phase 3pH Air 700m³/h Rated Input 7.5kW





H - Classified - in compliance with the highest international standard 'H'.







Hedge Trimmers

For professional and home use.



522HDR60S Engine Bar 21 7 c c 60cm Weight 5.1kg

122HD60 / 122HD45 Engine Bar 21.7cc / 21.7cc 59cm / 45cm Weight 4.9kg / 4.7kg

322HD60 Engine Bar 21.7cc 60cm Weight 5.2kg

520iHD60

Bar

Blowers/Vacuum High blowing capacity.

Powerful backpack model for large assignments.



125B / 125BVx Engine 28cc / 28cc Noise level 94dB / 94dB 4.3kg / 4.3kg Weight

525BX Engine Noise level Weight

25cc

91dB

4.3kg

570BTS Engine Noise level 65.6cc 99dB Weight 11.2kg

Battery Series





Engine

Length

Weight

36V 3.0kg

535iRXT Engine Weight

36V 4.9kg



36V 25cm - 30cm

3.1kg - 5kg

530iPT5 / 530iP4 / 530iPX

525iB Engine 36V 82dB(A) Noise

36V Engine 60cm 5.1kg Weight



BLi10 Battery 2Ah 36V

535iXP 36V Engine Bar 14" 2.6kg Weight



Battery charger



I CI41i Engine 36V Cut Width 41cm

Chippers & Shredders

With the revolutionary 'Disc-Blade' chipping system.



Ħ **Husqvarna®**

OUTDOOR PRODUCTS

Push & Ride-On Mowers Models for all lawn mowing jobs.



LB553SE / LB548SE Engine 160cc Cut width 53cm / 48cm



Z254F / Z242E / Z248F / Z242F Engine 24hp / 21.5hp / 23hp / 21.5hp Cut width 137cm / 107cm / 122 cm / 107cm



LC19AP / LC19SP / LC19A Engine 161cc Cut width 48cm



TS354 / TS342 17.9kW / 16.0kW Engine Cut width 137cm / 107cm



R316TsXAWD / R316TX Engine 603cc Cut width 94-112 cm



тс242тх / тс238 16.0kW / 13.4kW Engine Cut width 108cm / 96cm



P525D / P524 Engine 1123cc / 726cc Cut width 132-155 cm / 112-122 cm

Chainsaws Performance, comfort & ergonomics. Models for professionals & property owners.



390XP / 395XP / 3120XP 88cc / 94cc / 118cc 24" / 24" / 28" Engine Bar Weight 7.3kg / 7.9kg / 10.4kg



435 e-series II 40.9cc 16" Engine Weight 4.4kg

324R

Engine Weight

525RS

Engine Weight 5kg

25.0cc

25.4cc

5.5kg



440 e-series II 41.0cc 16' 4.4kg



562XP / 550XP / 572XP 60cc / 50cc / 70cc 20" / 16" / 20" 6.1kg / 4.9kg / 6.6kg Engine Bar Weight



445 e-series II Engine 45.7cc Bar 18" Weight 5.1kg



T540XP II / T525 / 27cc Engine 37.7cc, Bar 3.9kg / 2.7kg Weight



450 e-series II Engine 50.2cc Bar 20" Bar Weight 5.1kg



455 Rancher AT Engine Bar 55.5cc 20" Weight 5.9kg



Engine Bar 20" 5.8kg Weight

Bar









535RXT 34.6cc Engine 34.6c Weight 6.7kg

535RJD

Engine Weight 25.4cc

4.9kg



545RXT-AT 45.7cc Engine Weight 8.6kg



ACCESS EQUIPMENT & MATERIALS HANDLING



CONSTRUCTION PRODUCTS OUTDOOR EQUIPMENT





COMPACTION EQUIPMENT

SURFACE PREPARATION

& DUST CONTROL



HEAVY COMPACTION



MINI EXCAVATORS & MINI DUMPERS

MOWHITEMAN

LIGHT TOWERS & DUST CONTROL

KOSHIN

PUMPS

GreenMech

CHIPPERS & SHREDDERS

FOSROC

CONSTRUCTION PRODUCTS

BIEMMEDUE

DEHUMIDIFIERS

AERIAL WORK PLATFORMS

ORM

Denyo

GENERATORS & WELDERS

CONCRETING EQUIPMENT

lextoo

HAND TOOLS

🖹 MARUZEN

BREAKERS & POWER PACKS

POWER TROWELS

HATZ

DIESEL ENGINES



MINI DUMPERS



MATERIALS HANDLING

PRC

GENERATORS & CONCRETE MIXERS & WATERBLASTERS



CONCRETE MIXERS

SELWOOD

CONTRACTOR PUMPS

ALMACRAWLER

ACCESS EQUIPMENT

NAKIUEX

CONSTRUCTION EQUIPMENT

UFF<u>BELT</u>

PORTABLE CONVEYORS

POWERED by

Shizuoka

INDUSTRIAL HEATERS

HONDA

ENGINES PUMPS GENERATORS

CONCRETE & MORTAR MIXERS

PARTS SERVICE

POWER SCREED

We are proud of the back-up service we offer to customers. The importance of stocking genuine spare parts for all the equipment we supply is a high company priority.



YRCO.CO.NZ