



Husqvarna DM 430

DM 430 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed, especially with large diameter core bits. Recommended diameter 100-450 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services™ for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling, stitch drilling and when you need cut close to corners.



Optimised RPM's

Enables high drilling performance.



Ergonomic

Equipped with a carrying handle for easy transport and handling.



Sturdy and durable

Equipped with an aluminium housing and the protective carrying handle ensures rough handling.



Embedded Connectivity

An enhanced version of Husqvarna Fleet Services™. Enables data analytics and insights into the health of the machine.




FEATURES

- Sturdy and durable
- Ergonomic
- Optimised RPM's
- Embedded Connectivity
- Quick connection
- Quick-release washer
- Functional design
- The LED indicator shows the load of the machine, allowing the operator to always drill at maximum pressure, for best performance.
- The machine uses pulsation to warn you of an approaching overload. This increases productivity and extends product life.
- Reliable gearbox
- To facilitate making a starter hole, speed is reduced by half using the Smart Start® button.
- Drilling holes in stepless adjustable angles.
- Drilling for installation of stair rails, fences, etc.
- Drilling horizontally.
- Drilling multiple holes next to each other to make openings.
- Drilling upwards and downwards.
- Drilling for water evacuation.

Technical Specifications

MOTOR	
Electronic product	Yes
Frequency	50-60 Hz
Voltage	220-240 V
Rated input power	3.2 kW
DRILLING EQUIPMENT	
Drill bit diameter with stand, max	450 mm
Recommended drill bit diameter, min	100 mm
SPECIFICATIONS	
Water pressure, max	3 bar
Spindle thread, outer	CR1-28
TRANSMISSION	
Number of gearbox speeds	3
DIMENSIONS	
Water connector	G 1 / 4"
Weight	15.5 kg
Product size length	23 mm
Product size width	138 mm
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	92 dB(A)
PACKAGING	
Packaging length	665 mm
Packaging width	255 mm
Packaging height	300 mm

ACCESSORIES



SPACER FOR QUICK MOUNTING
579 50 10-02



DRILL SNAP
531 07 46-74



HUSQVARNA DS 500
967 96 86-01



HUSQVARNA W 70 P
967 66 47-04



SLURRY RINGS WSR
593 56 30-01



SLURRY RINGS WSR
593 56 30-02



SLURRY RINGS WSR
593 56 30-03



SLURRY RINGS WSR
593 56 30-04



SLURRY RINGS WSR
593 56 30-05



SLURRY RINGS WSR
593 56 30-06



HUSQVARNA DS 50 GYRO
965 15 78-20



HUSQVARNA DS 50 GYRO
965 15 78-21



SLURRY COLLECTOR V-SHAPED
531 07 46-22



SLURRY COLLECTOR V-SHAPED
531 28 00-07



HUSQVARNA WT 15I
599 58 23-02



HUSQVARNA WT2GO
598 74 24-01



SLURRY COLLECTOR
531 28 03-29

DRILL MOTOR KEYS
544 97 00-05