ArbTrak 150 When you just need to get to difficult places





Customer category Landscaper • Estate Maintenance • Contractor

Probably the most versatile, go-anywhere, 150mm wood chipper on the market, complete with a highly manoeuvrable track system that will take you to all those hard to-get-to spots in all kinds of ground conditions. Fitted as standard with a Kubota Diesel 34hp, this has the same chipper and in-feed construction as the Arborist 150, that has set the standards for quietness of operation, durability and performance. The ArbTrak 150 is a key component of specialist professional contractors, who are focussed on maintaining difficult terrain and need extra traction and lower ground pressure in less than perfect conditions. Ground clearance is 274mm and therefore this machine is very agile and manoeuvrable.

The backbone of the ArbTrak 150s design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 970mm x 790mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through twin, hydraulically powered feed rollers, the patented electronically controlled No-Stress system automatically manages the throughput of material to maximise chipping efficiency.

Technical Specification...

ArbTrak 150 Technical Specification Richardson



Key features

- 150mm chipping capacity
- 34hp Kubota diesel engine
- Disc-blade chipping technology
- No-Stress power control
- Twin vertical hydraulic feed rollers
- High-speed track system
- Bottom-bar safety mechanism
- 1046kg weight





| Capacity | 150mm |
|------------------------|---------------|
| Engine Make | Kubota |
| Engine | 34hp |
| Fuel | Diesel |
| Tractor Required | n/a |
| Chipping Flywheel | Disc Type |
| Flywheel Speed | 1700rpm |
| Blades | 4 |
| Hydraulic Feed Rollers | Twin Vertical |
| Turntable | n/a |
| Power Control | No-Stress |
| Fuel Capacity (engine) | 27 L |
| Tyre Size (towed) | n/a |
| Spare Wheel | n/a |

| Tonnes per hour | 4.7 |
|------------------------|---------------|
| Infeed Chute Aperture | 970mm x 790mm |
| Infeed Throat Size | 150mm x 230mm |
| Discharge Chute | 280° Rotation |
| Hydraulic Oil Capacity | 30 L |
| Clutch | n/a |
| Hour Meter | Standard |
| Length (transport) | 3000mm |
| Width (transport) | 1171mm |
| Height | 2380mm |
| Weight | 1046kg |
| Sound Power LWA | 115dB(A) |
| Sound Pressure LPA | 92dB(A) |

Auckland Head Office 6-10 Parkway Drive, Mairangi Bay, Auckland Phone: (+64) 09 443 2436 Email: sales@yrco.co.nz

Auckland, Mt Wellington 20L Sylvia Park Road, Mt Wellington, Auckland Phone: (+64) 09 553 5470 Email: salesmtwell@yrco.co.nz Wellington 8 Broken Hill Road, Porirua, Wellington Phone: (+64) 04 212 2456 Email: saleswell@yrco.co.nz Christchurch 20 Nga Mahi Road, Sockburn, Christchurch Phone: (+64) 03 341 6923 Email: saleschch@yrco.co.nz

