

Arborist 200

Brute force and high output

YR Youngman
Richardson

GreenMech
The Professionals' Choice



Customer category

Contractor • Large Scale Forestry Clearance

Looking for even greater performance than that of a 150 mm machine, the Arborist 200 has to be on your shopping list. Powered by a 45hp Kubota diesel engine with masses of torque, pumping wood waste through a massive 200mm x 280mm letterbox, this is a machine that will impress arborists, tree surgeons and contractors, day-in, day-out. It's heavy-duty construction means it will stand the test of time and maintain a healthy residual value and a strong return on investment

The backbone of the Arborist 200s design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 1200mm x 840mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through twin, horizontal, hydraulically powered feed rollers, the patented electronically controlled No-Stress system automatically manages the throughput of material to maximise chipping efficiency.

Key features

- ⊙ 200mm chipping capacity
- ⊙ 45hp Kubota turbo diesel engine
- ⊙ Disc-Blade chipping technology
- ⊙ Twin, horizontal, hydraulic feed rollers
- ⊙ Bottom-bar Safety Mechanism
- ⊙ LED Lighting
- ⊙ No-Stress power control
- ⊙ Top control bar
- ⊙ 1260kg weight



Capacity	200mm
Engine Make	Kubota
Engine	45hp
Fuel	Diesel
Tractor Required	n/a
Chipping Flywheel	Disc Blade
Flywheel Speed	1500rpm
Blades	4
Hydraulic Feed Rollers	Twin Horizontal Hydraulic
Turntable	n/a
Power Control	No-Stress
Fuel Capacity (engine)	27 L
Tyre Size (towed)	175R13C
Spare Wheel	Optional

Tonnes per hour	7
Infeed Chute Aperture	1200mm x 840mm
Infeed Throat Size	200mm x 280mm
Discharge Chute	280° Rotation
Hydraulic Oil Capacity	27 L
Clutch	Optional
Hour Meter	On RDS control box
Length (transport)	3990mm
Width (transport)	1440mm
Height	2695mm
Weight	1260kg
Sound Power LWA	116dB(A)
Sound Pressure LPA	92dB(A)
Bottom-bar Safety Mechanism	Standard

Auckland Head Office
6-10 Parkway Drive,
Mairangi Bay, Auckland
Phone: (+64) 09 443 2436
Email: sales@yrco.co.nz

Auckland, Mt Wellington
20L Sylvia Park Road,
Mt Wellington, Auckland
Phone: (+64) 09 553 5470
Email: salesmtwell@yrco.co.nz

Wellington
8 Broken Hill Road,
Porirua, Wellington
Phone: (+64) 04 212 2456
Email: saleswell@yrco.co.nz

Christchurch
20 Nga Mahi Road,
Sockburn, Christchurch
Phone: (+64) 03 341 6923
Email: saleschch@yrco.co.nz