

FEATURES

- Increased performance
- Safer operation
- Superior remote control
- Live operating surveillance
- Compact and powerful in relation to the low weight. Its large footprint enables a high workload.
- With a compact design, only 31 in. in width the machine can access many working locations.
- With reduced need to move the machine you minimize set-up time and can easily operate in confined spaces.
- Gives good access to confined spaces and high maneuverability.
- The set-up of the arm system combined with the software gives smooth and precise positioning of the tool.
- The outriggers are individually controlled, this combined with a large footprint provides superior stability enabling high workload on various surfaces.
- The arm has a stable, durable design with low weight.
- The remote control can be worn over the shoulder thanks to an ergonomic bar.
- Our tools are predefined in the menu for highest performance of the tools. You can set parameters for your own individual preferences as well as for the arm system.
- The low height provides good views over the machine and the low center of gravity contributes to a stable operation.
- The castered baseplate has integrated lift bails.
- Thanks to the covers of the main body, which are easy to open and detach for fast servicing.
- For high durability and strength which enables high workload and efficiency.
- The powerful and strong LED lights provide high working efficiency and good control of the work.
- No manual greasing means longer service intervals.
- Hydraulic feature P1 installed from factory

Technical Specifications

BATTERY	
Battery capacity	5.1 Ah
Battery type	Li-Ion
HYDRAULICS	
Oil capacity	42 l
Hydraulic oil flow	75 l/min
Hydraulic pressure, max	250 bar
SPECIFICATIONS	
Telescopic arm	No
Range of wireless transmission	Up to 300 m
Signal transmission	Radio or cable
Radio	2.4 GHz
DIMENSIONS	
Reach (forward)	4.5 m
Reach (up)	4.8 m
Product size length	2442 mm
Product size width	780 mm
Product size height	1367 mm
Weight	1750 kg
PACKAGING	
Packaging length	3030 mm
Packaging width	950 mm
Packaging height	1920 mm
Packaging volume	5140.6 dm ³