# SCREEDSAVER ELITE





### SCREEDSAVER ELITE

Meet the SCREEDSAVER® ELITE, the best-selling offering in the Ligchine SCREEDSAVER line of innovative, labor-saving machines. The SCREEDSAVER ELITE is loaded with features including all-wheel drive, heavy-duty boom reaching 18 feet, twin 33-gallon on-board fluid tanks and an on-board pressure washer for clean-up. The game changing side-shift head makes it easier to screed around stick-ups in slabs with pinpoint accuracy. The ELITE is the most versatile laser guided screed machine from Ligchine.

#### **Key Features:**

The SCREEDSAVER ELITE includes a 11 foot sideshift screed head, selectable all-wheel drive, revised remote control system, and an on-board pressure washer.

#### Engine:

Kubota V1505, 4-cylinder, diesel engine.

#### Lighting System:

Front and rear LED pod lighting.

#### Diagnostic Display:

Readily accessible Parker touch-screen display with full diagnostics capability.

#### Transport:

Ease of transport with a 3/4 ton pickup truck and trailer.

**MACHINE DETAILS & SPECS** 

# LIGCHINE

## SCREEDSAVER ELITE



| Engine Size   | Kubota V1505, 4-cylinder / 3,000 rpm, diesel            |
|---|---|
| Machine Size (retracted)                              | W-5' 9" (1.79 m) x L-14' 6" (4.45 m) x H-5' 5" (1.67 m) |
| Machine Weight  | 6,540 lbs. (Including screed head and full tanks)       |
| Steering System (hydraulic)                           | Front-wheel steering                                    |
| Drive System (hydraulic)                              | 4 wheel proportional                                    |
| Parallel to the Pour Driving Capable                  | Yes – 360 degree drive frames (zero turn capable)       |
| Lighting System                                       | 2 forward and 1 rear facing LED light pods              |
| Machine Operation Control                             | 100% Wireless Remote Control                            |
| Coverage per screed pass (no overlap)                 | 216 sq. ft. (20 sq. m)                                  |
| Side-shift Screed Head Length / Travel Distance       | 11' (3.4 m) / 22"                                       |
| Boom Reach  | 18' (5.5 m)   |
| Self-contained Concrete Additive Sprayer System       | Standard  |
| Diagnostics (hydraulic, electrical, engine and laser) | Standard- Parker MD4, 7" touch-screen color display     |
| Transport with Pickup Truck and Trailer               | Yes   |
| Machine Length When in Trailer Mode                   | 23' (7.01 m)  |
| Grade/Slope/Dual Slope control (standard)             | Topcon LS-B110  |
| Contoured Slope 3D Capable (optional)                 | Topcon 3D mmGPS Satellite control or LPS Robotic        |

