



Husqvarna®



SKIN ONLY

## The new battery powered Husqvarna DM 540i drill motor – cordless and optimal for handheld drilling

Husqvarna is introducing the DM 540i battery drill motor which fits in narrow corners, has low weight, is optimally balanced and easy to use for an even more productive workday. DM 540i battery drill motor is optimised for handheld drilling for most materials especially reinforced concrete with diameters up to Ø 75 mm/3 inches. Part of a flexible system and suitable for both wet drilling in a good match to WT 15i water tank or dry cutting. Also suitable to mount on a DS 150 drill stand for diameters up to Ø 100 mm/4 inches. Battery and charger sold separately, pair with a BLi 200 or BLi 300 battery and a QC 500 charger.



### Everything in its right place

DM 540i is available with a practical custom made transportation box, with compartments fitting the motor, two batteries, charger and water coupling, 2 different keys (24 mm, 32 mm), 5/8 – 11 UNC adapter and vacuum kit.



### Power on the go

DM 540i is developed for Husqvarnas BLi-battery system. The recommended battery is BLi 300 and BLi 200 – and they are all compatible with any other Husqvarna BLi-battery equipment.

### Specially developed drill bits

The new range of thin walled Husqvarna drill bits provide a better utilization of the machine and battery power of the DM540i. Thanks to the diamond specification you will experience a faster drilling and smoother cut. The range includes drills for both wet and dry drilling. Roof top segment design on drill diameter larger than 50 mm to get an easy and smooth start.



### Wet or dry

The drill motor can be used for both wet and dry cuts, with an easy switch from water hose with connector, to attachment for dust extractors. Or vice versa. Perfect for combination with other BLi-battery Husqvarna equipment like the WT 15i water tank or the dust extractor DE 110i.



# SPECIFICATIONS

## Description

Dimensions (L x H):	445 x 272 mm
Weight:	4.9 kg (6.8 kg including BLi 300)
Motor type:	BLDC (brushless)
Output power on spindle shaft:	1200 W
Voltage:	36 V
Drill diameter in concrete:	Ø 50–100 mm (mechanical gear 1), Ø 15–50 mm (mechanical gear 2)
Model No:	970493701
EAN Number:	7392930963825
Packaging dimensions with packaging:	220mm (w) x 600mm (d) x 400mm h)

## RELATED PRODUCTS AND ACCESSORIES



### BATTERIES BLi 200/300

4-LED charge level indicator. Rechargeable more than 1500 times. Capacities: 5.2 / 9.4 Ah.



### CHARGER QC 500

Quick charging unit with 2-LED status indicator and active battery cooling for minimum charge time and longer battery life. Weight 1.5 kg, main voltage 110–240 V, output power 500 W, charging times BLi 200 – 30/50 min\*, BLi 300 – 35/60 min\*.

\*Charging times refers to 80/100%



### DS 150 DRILL STAND

Versatile and lightweight drill stand. DS 150 is suitable for jobs requiring fast setup, for example light core drilling up to 150 mm diameter. With Ø 60 mm coupling, fitting the DM 540i.



### WATER TANK WT 15i

15 l water tank. Battery powered, compatible with the Husqvarna 36 V BLi-system.



### DUST EXTRACTOR DE 110i

This H-class Dust Extractor is powered by Husqvarna's own BLi batteries and is an excellent match for the DM 540i drill motor as well as other handheld equipment within the BLi platform. DE 110i is compact and easy to transport, yet powerful. It features a user friendly HMI, SmartFlow that automatically adjusts the airflow and the entire machine can be hosed down with water for efficient decontamination.

COMING SOON



### TRANSPORTATION BOX

Transportation box, with compartments fitting the DM 540i drill motor, two batteries, charger and water coupling, 2 different keys (24 mm, 32 mm), 5/8 – 11 UNC adapter and vacuum kit.