



Husqvarna FS 3500 G

FS 3500 G is a self-propelled floor saw ideal for small to medium patch and service jobs. Equipped with a 27.5 kW Kohler gasoline engine. It is lightweight, low profiled, easy to manoeuvre and service. The Poly-V belt together with a self-adjusting belt tensioner ensures stable power levels at the blade shaft. Cutting depth capacity up to 311 mm with a 750 mm diamond blade. Comes standard with adjustable handle bars, engine tachometer and hour meter. Water pump kit and light kit available as options.



Automatic belt tensioner and Poly-V belt

Offers no maintenance, lower cost of ownership, consistent power and increased production.




Clam cleat pointer rope holder

Reduces pointer rope damage and holds front pointer at a set height.



Classic and intuitive control panel

Includes engine tachometer and water safety system.



Options include LED light-kit and water pump kit

LED offers lower electrical power consumption and water pump kit allows cutting with low water pressure and flow.



FEATURES

- Automatic belt tensioner and Poly-V belt
- Classic and intuitive control panel
- Clam cleat pointer rope holder
- Options include LED light-kit and water pump kit
- Well-balanced design with a low profile gives you high visibility and makes it easy to handle and transport.
- Two-position handle bar for operator comfort
- For easy operation and comfort.
- Effective transfer of power to blade shaft
- Dependable design
- Flexible blade mounting

Technical Specifications

ENGINE

Output power (As rated by the engine/motor manufacturer)	28.3 kW
Output power at tool shaft	21.6 kW
Engine cooling	Air
Fuel tank volume	23.8 l
Cylinders	2
Number of strokes	4-stroke engine
Exhaust emissions (CO2 EU V)	898 g/kWh
Fuel tank volume	6.3 gal (US)

CUTTING EQUIPMENT

Arbor diameter	25.4 mm
Blade depth control	Electric hydraulic
Blade diameter, max	650 mm
Cutting depth, max	262 mm

TRANSMISSION

Transmission speed reverse	0 m/min
Transmission speed forward	167 m/min

DIMENSIONS

Product size length	1168 mm
Product size width	807 mm
Product size height	1152 mm
Weight	450 kg