

ELECTRIC SCISSOR LIFTS - ELECTRIC DRIVE

0808E AC (2732E)

Compliant with AS 1418 · 10 standards



PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly


- Higher work efficiency
- Environmental protection, zero emissions

Reduced Maintenance Costs

- The short design of sliding rail makes debris easy to clean
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

Reliable Performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding rail designed for anti-scratch



Standard Features		
2WD×2WS	AGM maintenance-free battery	Telematic ready
Non-marking tires	Proportional control	Battery isolator
Emergency stop	Forklift pockets and lifting points	Secondary guarding system
Flashing beacon	Automatic pothole protection	White noise alarm
Foldable guardrail	Bumper rails	Fault diagnosis system
Drivable at full height	Weight management system	Manual storage box
Options & Accessories		
Wheel nut indicators	Panel lifting system	Telematic device
Fire extinguisher/Bracket	Mine spec	AC power to platform
Pipe lifting system		

SINOBOOM™

PARTNERS IN ACCESS™

🌐 **SINOBOOM.AU** | 📞 **03 8905 1550**




HO: BRISBANE – 39 ALTA ROAD, CABOOLTURE QLD 4510 | SYDNEY – 1/3 VOYAGER CT, GLENDENNING NSW 2761
MELBOURNE – 32-34 MARNI, DANDENONG SOUTH VIC 3175

ELECTRIC SCISSOR LIFTS - ELECTRIC DRIVE

0808E AC (2732E)

Compliant with AS 1418 · 10 standards

Model	0808E AC (2732E)
Dimensions	
Max Working Height (Indoor/Outdoor)	10.1 m/8 m (33'2"/26'3")
A Max Platform Height (Indoor/Outdoor)	8.1 m/6 m (26'7"/19'8")
B Platform Extension	0.9 m (3')
C Length-Stowed	2.46 m (8')
D Width-Stowed	0.83 m (2'8.7")
E Height-Stowed (Rails Folded)	1.96 m (6'5")
E Height-Stowed (Rails Unfolded)	2.36 m (7'9")
F Wheelbase	1.88 m (6'2")
Ground Clearance (Pothole Guard Stowed)	0.1 m (4")
Ground Clearance (Pothole Guard Deployed)	0.025 m (0.98")
Platform Size (L×W×H)	2.3 m×0.8 m×1.1 m (7'6.5"×2'7.5"×3'7")
Performance	
Platform Capacity	250 kg (551 lbs)
Extension Platform Capacity	120 kg (265 lbs)
Max Platform Occupants (Indoor/Outdoor)	2 persons /1 person
Drive Speed (Stowed)	0 ~ 4 km/h (0 ~ 2.5 mph)
Drive Speed (Raised)	0 ~ 0.8 km/h (0 ~ 0.5 mph)
Lift Time (Rated Load)	30 s~35 s
Lower Time (Rated Load)	34 s~39 s
Gradeability	25%
Max Allowable Inclination (front-to-back/side-to-side)	3° /1.5°
Turning Radius (Inside/Outside)	0m /2.1 m (0/6'10.7")
Tyre Size/Type	380×125 mm (15×5')/solid
Power	
Drive×Steer	2 WD×2 WS
Power Source (V/kW)	24 V/3.3 kW
Drive Motor (V/kW)	24 V AC /0.7 kW
Hydraulic Tank Capacity	15L (3.3 gal (UK) / 4.0 gal (US))
Batteries	24 V,220 Ah (AGM)
Charger (Input/Output)	100 ~ 240 V AC/30 A
Weight	
Weight (Indoor/Outdoor)	2,265 kg (4,994 lbs)
Standards Compliance	AS 1418 · 10



Auckland, Head Office
6-10 Parkway Drive,
Mairangi Bay,
Auckland
(+64) 09 443 2436
sales@yrco.co.nz

Auckland, Mt Wellington
20L Sylvia Park Road,
Mt Wellington,
Auckland
(+64) 09 553 5470
salesmtwell@yrco.co.nz

Waikato
3/31 Chafer Place,
Te Rapa,
Hamilton
(+64) 07 595 0245
saleswaikato@yrco.co.nz

Wellington
8 Broken Hill Road,
Porirua,
Wellington
(+64) 04 212 2456
saleswell@yrco.co.nz

Christchurch
20 Nga Mahi Road,
Sockburn,
Christchurch
(+64) 03 341 6923
saleschch@yrco.co.nz

4C+
CELEBRATING
OVER 40 YEARS
IN BUSINESS

YR Youngman
Richardson