

PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly


- Higher work efficiency
- Environmental protection, zero emissions

Reduced Maintenance Costs

- The short design of sliding rail makes debris easy to clean
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

Reliable Performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding rail designed for anti-scratch






Standard Features		
2WD × 2WS	AGM maintenance-free battery	Telematic ready
Non-marking tires	Proportional control	Battery isolator
Emergency stop	Forklift pockets and lifting points	Secondary guarding system
Flashing beacon	Automatic pothole protection	White noise alarm
Foldable guardrail	Bumper rails	Fault diagnosis system
Drivable at full height	Weight management system	Manual storage box
Options & Accessories		
Wheel nut indicators	Panel lifting system	Telematic device
Fire extinguisher/Bracket	Mine spec	AC power to platform
Pipe lifting system		

ELECTRIC SCISSOR LIFTS - ELECTRIC DRIVE

1012E AC (3346E)

Compliant with AS 1418 · 10 standards

Model	1012E AC (3346E)
Dimensions	
Max Working Height(Indoor/Outdoor)	12 m (39'4.5")
A Max Platform Height(Indoor/Outdoor)	10 m (32'10")
B Platform Extension	0.9 m (3')
C Length-Stowed	2.45 m (8')
D Width-Stowed	1.17 m (3'10")
E Height-stowed (Rails Folded)	1.86 m (6'1")
E Height-stowed (Rails Unfolded)	2.48 m (8'1.6")
F Wheelbase	1.88 m (6'2")
Ground Clearance(Pothole Guard Stowed)	0.1 m (4")
Ground Clearance(Pothole Guard De-ployed)	0.025 m (0.98")
Platform Size (L×W×H)	2.30 m×1.15 m×1.1 m (7'6.5"×3'9"×3'7")
Performance	
Platform Capacity	320 kg (705.6 lbs)
Extension Platform Capacity	120 kg (265 lbs)
Max Occupants (Indoor/Outdoor)	2 Persons/1 Person
Drive Speed (Stowed)	0 ~ 4 km/h (0 ~ 2.5 mph)
Drive Speed (Raised)	0 ~ 0.8 km/h (0 ~ 0.5 mph)
Lift Time (Rated Load)	53s~58s
Lower Time (Rated Load)	46s~57s
Gradeability	25%
Max Allowable Inclination (front-to-back/side-to-side)	3° /1.5°
Turning Radius (Inside/Outside)	0 / 2.35 m (0 / 7'8.5")
Tire Spec/Type	380×125 mm/solid (15"×5")
Power	
Drive × Steer	2WD×2 WS
Power Source (V/kW)	24V DC , 3.3 kW
Drive Motor (V/kW)	24 V AC / 0.7 kW
Hydraulic Tank Capacity	15 L (3.3 gal (UK)/4.0 gal (US))
Batteries	24 V,220 Ah (AGM) 25.6 V, 200 Ah (Lithium battery)
Charger (Input/Output)	100 ~ 240 V AC/30 A
Weight	
Weight (Indoor/Outdoor)	2,815 kg (6,206 lbs)
Standards Compliance	AS 1418 · 10



Auckland, Head Office
6-10 Parkway Drive,
Mairangi Bay,
Auckland
(+64) 09 443 2436
sales@yrco.co.nz

Auckland, Mt Wellington
20L Sylvia Park Road,
Mt Wellington,
Auckland
(+64) 09 553 5470
salesmtwell@yrco.co.nz

Waikato
3/31 Chafer Place,
Te Rapa,
Hamilton
(+64) 07 595 0245
saleswaikato@yrco.co.nz

Wellington
8 Broken Hill Road,
Porirua,
Wellington
(+64) 04 212 2456
saleswell@yrco.co.nz

Christchurch
20 Nga Mahi Road,
Sockburn,
Christchurch
(+64) 03 341 6923
saleschch@yrco.co.nz

