

PRODUCT HIGHLIGHTS**High Capacity**

- Plus series boom lifts holds up to 454kg (restricted)/300kg (restricted)/250kg (unrestricted) platform capacity allowing you to carry up to 3 occupants plus material and tools to get your job done easily.

Intelligent Maintenance

- Industry leading 7" screen displays faults and status information, for easy reference. Workers can complete tasks under the remote guidance of qualified service technicians. Convenient for fleet managers to quickly access live machine and maintenance information

Precision Performance

- The upper control box is equipped with 3 full-proportional handles for gradual control of boom lifting, telescoping, turntable rotation and driving speed. Operate with smooth starting and stopping and precision approach to your worksite target





Standard Features		
4WD×2WS	Fault diagnosis system	Telematic ready
Hydraulic platform leveling	Display screen	Battery isolator
Flashing beacon	Emergency lowering system	Secondary guarding system
Proportional control	Weight management system	White noise alarm
Tilt protection system	Non-marking tires	Half-mesh for platform
Manual storage box	Generator	
Options & Accessories		
Wheel nut indicators	Mine spec	Telematic device
Fire extinguisher/Bracket	AC power to platform	Driving lights
Pipe lifting system		

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB32JN PLUS (TB1060JN PLUS)

Compliant with AS 1418 · 10 standards

Model	TB32JN Plus (TB1060JN PLUS)
Dimensions	
Max Platform Height	32.3 m (105'12")
Max Working Height	34.3 m (112'6")
Max Horizontal Reach(Restricted/Restricted/Unrestricted)	17.9 m/20.0 m/20.9 m (58'9"/65'7"/68'7")
A Machine Length (Stowed/Transport)	12.76 m/9.73 m (41'10"/31'11")
B Machine Width (Stowed/Transport)	2.49 m/2.49 m (8'2"/8'2")
C Machine Height (Stowed/Transport)	2.88 m/2.88 m (9'5"/9'5")
D Wheelbase	3.0 m (9'10")
Ground Clearance	0.46 m (1'5.1")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
Performance	
Max Platform Capacity (Restricted/Restricted/Unrestricted)	454 kg/300 kg/250 kg (1,000lbs/661lbs/551lbs)
Max Platform Occupants (Restricted/Restricted/Unrestricted)	3 persons/2 persons/2 persons
Drive Speed (Stowed/Raised)	0 ~ 4.8 km/h (0 ~ 3 mph) 0 ~ 1.1 km/h (0 ~ 0.68 mph)
Gradeability	45%
Turntable Rotation	360° /Continuous
Platform Rotation	160°
Tilt Rating	5°
Turning Radius (Inside/Outside)	3.65 m/6.91 m (12'/22'8")
Turntable Tail-Swing	1.45 m (4'8")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	385/65D22.5 (foam-filled) 385/65-24/10 (solid) 15-625 (foam-filled)
Power	
Drive × Steer	4WD × 2WS
Engine	54 kW/2400 rpm/ QSF2.8t3TC72/Cummins/China T3. EU stage III 55.4 kW /2600 rpm/ TD2.9 L4/Deutz/EU stage V, EPA Tier 4F
Hydraulic Tank Capacity	180 L (39.6gal(UK)/47.6gal(US))
Diesel Tank Capacity	150L(33.0 gal(UK)/39.6 gal(US))
System Voltage	12 VDC
Weight	
Weight	17,460 kg (38,493lbs)
Standards Compliance	AS 1418 · 10



Auckland, Head Office
6-10 Parkway Drive,
Mairangi Bay,
Auckland
(+64) 09 443 2436
sales@yrco.co.nz

Auckland, Mt Wellington
20L Sylvia Park Road,
Mt Wellington,
Auckland
(+64) 09 553 5470
salesmtwell@yrco.co.nz

Waikato
3/31 Chafer Place,
Te Rapa,
Hamilton
(+64) 07 595 0245
saleswaikato@yrco.co.nz

Wellington
8 Broken Hill Road,
Porirua,
Wellington
(+64) 04 212 2456
saleswell@yrco.co.nz

Christchurch
20 Nga Mahi Road,
Sockburn,
Christchurch
(+64) 03 341 6923
saleschch@yrco.co.nz

