

## ELECTRIC SCISSOR LIFTS

# 0407SE (1530SE)

Compliant with CE/AS/CSA/AS/EAC/KCS standards



### PRODUCT HIGHLIGHTS

- Easily passes through standard doors and can access elevators
- The short design of sliding rail makes debris easy to clean
- Bumper rail and indented sliding rail designed for anti-scratch
- DC motor drive, giving a longer runtime



| Standard Features       |                                     |                           |
|-------------------------|-------------------------------------|---------------------------|
| 2WD×2WS                 | Maintenance-free battery            | Fault diagnosis system    |
| Non-marking tires       | Proportional control                | Emergency lowering system |
| Emergency stop          | Electrophoretic painting            | Tilt protection system    |
| Flashing beacon         | Forklift pockets and lifting points | Overload sensing system   |
| Foldable guardrail      | Automatic pothole protection        | Manual storage box        |
| Drivable at full height | Bumper rails                        | Auto braking system       |
| White noise Alarm       | Trackunit-ready connector           |                           |
| Options & Accessories   |                                     |                           |
| RCBO                    | Battery isolater                    |                           |
| AC power to platform    | EQSS/Protector                      |                           |

**SINOBOOM™**

**PARTNERS IN ACCESS™**




**SINOBOOM.COM | SALES@SINOBOOM.COM**  
32-34 Marni Street, Dandenong South, VIC Australia 3175

# ELECTRIC SCISSOR LIFTS

## 0407SE (1530SE)

Compliant with CE/ANSI/CSA/AS/EAC/KCS standards

| Model                                                  | 0407SE (1530SE)                            |
|--------------------------------------------------------|--------------------------------------------|
| <b>Dimensions</b>                                      |                                            |
| Max Working Height(Indoor/Outdoor)                     | 6.5 m/5.8 m (21'3.9"/19')                  |
| A Max Platform Height(Indoor/Outdoor)                  | 4.5 m/3.8 m (14'9.2"/12'5.6")              |
| B Platform Extension                                   | 0.6 m (2')                                 |
| C Length-Stowed                                        | 1.42 m (4'7.9")                            |
| D Width-Stowed                                         | 0.76 m (2'5.9")                            |
| E Height-Stowed (Rails Folded)                         | 1.67 m (5'5.8")                            |
| E Height-Stowed (Rails Unfolded)                       | 1.97 m (6'5.6")                            |
| F Wheelbase                                            | 1.11 m (3'7.7")                            |
| Ground Clearance (Pothole Guard Stowed)                | 0.061 m (2.4")                             |
| Ground Clearance (Pothole Guard Deployed)              | 0.02 m (0.75")                             |
| Platform Size (L×W×H)                                  | 1.34 m×0.7 m×1.1 m<br>(4'4.8"×2'3.6"×3'7") |
| <b>Performance</b>                                     |                                            |
| Platform Capacity                                      | 240 kg (529 lbs)                           |
| Extension Platform Capacity                            | 115 kg (254 lbs)                           |
| Max Platform Occupants (Indoor/Outdoor)                | 2 Persons (Indoor)<br>1 Person (Outdoor)   |
| Drive Speed (Stowed)                                   | 0~4 km/h (0~2.5 mph)                       |
| Drive Speed (Raised)                                   | 0~0.8 km/h (0~0.5 mph)                     |
| Lift Time (Unloaded)                                   | 20s~23s                                    |
| Lower Time (Unloaded)                                  | 25s~27s                                    |
| Gradeability                                           | 25%                                        |
| Max Allowable Inclination (front-to-back/side-to-side) | 3°/1.5°                                    |
| Turning Radius (Inside/Outside)                        | 0.3 m/1.35 m (12"/4'5")                    |
| Tire Size/Type                                         | 255×76 mm (10×3") /solid                   |
| <b>Power</b>                                           |                                            |
| Drive×Steer                                            | 2 WD×2 WS                                  |
| Power Source (V/kW)                                    | 24 V/2.2 kW                                |
| Drive Motor (V/kW)                                     | 24 V DC/0.4 kW                             |
| Hydraulic Tank Capacity                                | 4 L (0.9 gal (UK)/1.05 gal(US))            |
| Batteries                                              | 24 V,120 Ah (Lead acid battery)            |
| Charger (Input/Output)                                 | 100~240 V AC/15 A                          |
| <b>Weight</b>                                          |                                            |
| Weight (Indoor/Outdoor)                                | 880 kg (1,941 lbs)                         |
| Standards Compliance                                   | CE/ANSI/CSA/AS/EAC/KCS                     |



**Auckland, Head Office**  
6-10 Parkway Drive,  
Mairangi Bay,  
Auckland  
(+64) 09 443 2436  
sales@yrco.co.nz

**Auckland, Mt Wellington**  
20L Sylvia Park Road,  
Mt Wellington,  
Auckland  
(+64) 09 553 5470  
salesmtwell@yrco.co.nz

**Waikato**  
3/31 Chafer Place,  
Te Rapa,  
Hamilton  
(+64) 07 595 0245  
saleswaikato@yrco.co.nz

**Wellington**  
8 Broken Hill Road,  
Porirua,  
Wellington  
(+64) 04 212 2456  
saleswell@yrco.co.nz

**Christchurch**  
20 Nga Mahi Road,  
Sockburn,  
Christchurch  
(+64) 03 341 6923  
saleschch@yrco.co.nz

**4C+**  
CELEBRATING  
OVER 40 YEARS  
IN BUSINESS

**YR Youngman  
Richardson**