

PRODUCT HIGHLIGHTS

Precision Performance

- Platform control unit equips 3 joysticks featuring proportional control, which is easy to operate and reach the work targets

Intelligent Maintenance

- Industry leading 7" screen displays faults and status information, for easy reference, reducing service technician assistance. Workers can complete tasks under the remote guidance of qualified service technicians. Convenient for fleet managers to quickly access live machine and maintenance information



Safe and Reliable

- Machine equips safety Rexroth controller with dual backup CPU and compliant with ISO 13849, high performance level d, combined with dual channel sensors offering an extremely safe redundancy



Standard Features		
Proportional control with 3 joysticks	7-in display screen	4WD x 4WS
Electrical platform leveling	Automotive-grade sleeves for all pipes	Weighing system
Tilt protection system	160° platform rotation	Telematics-ready connector
Flashing beacon	170° jib rotation	Half mesh (For platform with swinging gate)
Footswitch	White noise alarm	
Secondary guarding device	Battery isolator	
Max tilt rating to 5°	2.44 m(8') platform with swing gate	
Options & Accessories		
AC power to platform		
Platform work light		

ENGINE POWERED TELESCOPIC BOOM LIFTS

TB58RJ PLUS(TB1900RJ PLUS)

Compliant with CE/EAC standards

Model	TB58RJ Plus (TB1900RJ Plus)
Dimensions	
Max Platform Height	57.9 m (190')
Max Working Height	59.9 m (196'6")
Max Horizontal Reach(Restricted/Unrestricted)	20.01 m/24.4 m (65'8"/80'1")
A Stowed Length	20.07 m (65'10")
B Stowed Width	2.49 m (8'2")
C Stowed Height	3.1 m (10'2")
Stowed Length (Transport)	14.6 m (47'11")
Stowed Width (Transport)	2.49 m (8'2")
Stowed Height (Transport)	3.1 m (10'2")
D Wheelbase	5.2 m (17'1")
Ground Clearance	0.33 m (1'1")
Platform Size (L×W×H)	2.44 m×0.91 m×1.1 m (8'×3'×3'7")
Performance	
Max Platform Capacity(Restricted/Unrestricted)	454 kg/300 kg (1,000 lbs/661 lbs)
Max Platform Occupants(Restricted/Unrestricted)	2 persons
Drive Speed (Stowed)	4.5 km/h (2.8 mph)
Drive Speed (Raised)	0.48 km/h (0.3 mph)
Gradeability	45 %
Turntable Rotation	360 ° / Non-continuous
Platform Rotation	160 °
Jib Rotation	170 °
Tilt Rating	5 °
Turning Radius (Inside/Outside)	7.1 m/9.52 m (23'3.5" / 31'3")
Turntable Tail-Swing	3.58 m (11'9")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	445/50D710 24PR (Foam-filled)
Power	
Drive × Steer	4WD × 4WS
Engine	74 kw/2200 rpm/ YCF36100-T480/Yuchai/China Stage 4
Hydraulic Tank Capacity	405 L (89.1 gal(UK)/107 gal(US))
Diesel Tank Capacity	200 L (44 gal(UK)/52.8 gal(US))
System Voltage	12 VDC
Weight	
Weight	27,600 kg (60,848 lbs)
Standards Compliance	
CE/AS/EAC	



Auckland, Head Office
6-10 Parkway Drive,
Mairangi Bay,
Auckland
(+64) 09 443 2436
sales@yrco.co.nz

Auckland, Mt Wellington
20L Sylvia Park Road,
Mt Wellington,
Auckland
(+64) 09 553 5470
salesmtwell@yrco.co.nz

Waikato
3/31 Chafer Place,
Te Rapa,
Hamilton
(+64) 07 595 0245
saleswaikato@yrco.co.nz

Wellington
8 Broken Hill Road,
Porirua,
Wellington
(+64) 04 212 2456
saleswell@yrco.co.nz

Christchurch
20 Nga Mahi Road,
Sockburn,
Christchurch
(+64) 03 341 6923
saleschch@yrco.co.nz