



**MAKINEX®**



# Earth Moving 25hp Mini Stand-On Skid Steer

Model: SK25



**890mm Width**



**25 Horsepower**



**1 tonne Tipping Capacity**

The Makinex 25hp Mini Stand-On Skid Steer delivers powerful performance in a compact design, making it ideal for tight job sites where manoeuvrability is key. With a width of just 890mm, this versatile machine easily fits through narrow spaces while offering an impressive tipping capacity of 1,010 kg. Powered by a Kubota D1105 diesel engine, it delivers 24.7hp with smooth hydraulic operation, ensuring efficiency and reliability for heavy-duty lifting, grading, and material handling. The Makinex Skid Steer features premium, globally sourced parts, including Sumitomo Riko hydraulic lines (Japan), Bondioli & Pavesi pumps (Italy), Walvis control valves, Danfoss motors, and Donaldson filtration.



## IDEAL FOR:



**Tight-Space  
Excavation**



**Material  
Handling**



**Landscaping  
& Site Prep**



**Demolition & Debris  
Removal**



**Utility & Trenching  
Work**



**Agriculture &  
Farming**

## SPECIFICATIONS:

DIMENSIONS (STD)		PERFORMANCE	
Height to Bucket Hinge Pin, max	1.93 m	Ground drive speed, forward and reverse	6.3 km/h
Operating Height, max std.bucket	2.7 m	Ground pressure, 8 in (200 mm) tracks	0.35 bar
Height	1.3 m	Angle of Departure	22°
Length without Attachment	1.8 m	Tipping capacity	1010 kg
Length with Standard Bucket	2.5 m	Operating capacity (35% of tipping capacity)	354 kg
Ground Clearance	145 mm	Machine weight (no attachment, fluids full)	1230 kg
Ground Contact Length	960 mm	Auxiliary Hydraulic Flow	48 L/min
Width	890 mm	Auxiliary Hydraulic Pressure	180 Bar
<b>POWER</b>		Battery 12 V; 60 Ah	475 cold cranking amps @ -18°C
Engine Kubota D1105 diesel	EU Stage V/ EPA Tier 4 Final		
Number of cylinders	3	<b>FLUID CAPACITIES</b>	
Displacement	1.123 L	Fuel tank	34 L
Bore	78 mm	Engine oil, with filter	5 L
Stroke	78.4 mm	Hydraulic System	45 L
Gross power rating (per SAE J1955)	18.2 kW		
Rated engine speed	3000 rpm		




## FEATURES:



1. Stand-On Operator Platform



2. Compact 890mm Width



3. Kubota D1105 Diesel Engine




4. 1 Tonne Tipping Capacity



5. 48 L/min Hydraulic Flow




6. 6.3 km/h Travel Speed



7. Two sets of Quick Couplers



8. Wide selection of Attachments



9. Heavy Duty Frame



10. Easy access to all Engine Components

## MINI DUMPER RANGE



1. KATO CARRY 105



2. KATO CARRY 107



3. TUFFTRUCK

Auckland, Head Office  
6-10 Parkway Drive,  
Mairangi Bay,  
Auckland  
(+64) 09 443 2436  
sales@yrco.co.nz

Auckland, Mt Wellington  
20L Sylvia Park Road,  
Mt Wellington,  
Auckland  
(+64) 09 553 5470  
salesmtwell@yrco.co.nz

Waikato  
3/31 Chafer Place,  
Te Rapa,  
Hamilton  
(+64) 07 595 0245  
saleswaikato@yrco.co.nz

Wellington  
8 Broken Hill Road,  
Porirua,  
Wellington  
(+64) 04 212 2456  
saleswell@yrco.co.nz

Christchurch  
20 Nga Mahi Road,  
Sockburn,  
Christchurch  
(+64) 03 341 6923  
saleschch@yrco.co.nz

**40+**  
CELEBRATING  
OVER 40 YEARS  
IN BUSINESS

**YR** Youngman  
Richardson